

OIML Member State

The Netherlands

Number R49-1/2006-NL1-12.01 revision 9 Project number SO16202611 Page 1 of 5

Issuing authority NMi Certin B.V.

Person responsible: C. Oosterman

Applicant and Manufacturer

KROHNE Altometer Kerkeplaat 12 3313 LC Dordrecht The Netherlands

Identification of the

A water meter

certified type

Type : WATERFLUX 3070

Water meter intended for the metering of cold potable water and hot

water, model "WATERFLUX 3070", class 1 and 2.

Characteristics See page 2 and further

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

R49-1/2006 (E): Metrological and technical requirements

R49-2/2006 (E): Test methods **R49-3/2006 (E)**: Test Report format

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation identified above. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority

NMi/Certin B.V., OIML Issuing Authority NL

14 July 2015

C. Oosterman

Head Certification Board

NMi Certin B.V. Hugo de Grootplein 1 3314 EG Dordrecht the Netherlands T +31 78 6332332 certin@nmi.nl This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

Parties concerned can lodge objection against this decision, within six weeks after the date of submission, to the general manager of NMi (see www.nmi.nl).





OIML Member State

The Netherlands

Number R49-1/2006-NL1-12.01 revision 9 Project number SO16202611 Page 2 of 5

The conformity was established by the results of tests and examinations provided in the associated OIML Test Report(s):

- Number R49-1/2006-NL1-09.01 that includes 41 pages and 14 annexes;
- Number R49-1/2006-NL1-10.01 that includes 40 pages and 3 annexes;
- Number R49-1/2006-NL1-11.01 that includes 40 pages and 4 annexes;
- Number R49-1/2006-NL1-12.01 that includes 40 pages and 3 annexes;
- Number NMi-13200159-01 that includes 6 pages and 1 annex;
- Number NMi-15200645-01 that includes 21 pages and 4 annexes.

Identification of the certified pattern

Water meter intended for metering cold potable water and hot water, based on an electromagnetic principle, designed to measure forward and reverse flow, with (minimum) 0 D straight inlet and outlet, with no flow conditioner and equipped with an electronic calculating/indicating device. The construction of the water meter is recorded in the Documentation folder no. 10201-7.

Metrological characteristics:

Type : WATERFLUX 3070

Min/max admissible

temperature (°C)

0,1/50

Maximum pressure : 16 bar(g) for sizes DN200 and smaller

10 bar(q) for sizes DN250 and larger

Indicating range (m³) : 99.999.999

Orientation + + + + : All positions

Environmental class : C

Power supply : - Battery 3,6 V

Type - External battery pack with output 3,6 V
U_{battery} - FlexPower (optional for SW 5.0.1_ or higher)
10...30V DC or 110...230V AC / 50-60Hz

Software versions 4.0.4_; 4.0.10_; 4.0.11_; 4.0.12_; 4.2.2_; 4.2.4_; 4.2.5_; 4.2.6_;

4.3.0_, 4.3.1_, 5.0.1_, 5.0.2_, 5.0.3_

Note: In case of software version 4.3.1_ or lower the Field Current can only be set to 16 mA.

For software version 5.0.1_ or higher the different Field Currents can be selected and shall be

set to 16 mA.



OIML Member State The Netherlands

Number R49-1/2006-NL1-12.01 revision 9 Project number SO16202611 Page 3 of 5

Meter size	Accuracy class	+ + + + Flow rate [m³/h]+ + + + +				Ratio Q3/Q1
		Min. Q1	Trans. Q2	Perm. Q3	Over. Q4	
DN25	+ + 2+ + + + + +	0,025	0,04	+ 10 + +	+ 12,5 +	400
		0,04	+ 0,064 +	+ 16 + +	+ +20 +	
DN40	+ + 2 + + 2	0,0625	+ +0,1 +	+ 25 + +	+ 31,3 +	+ + + +
		+ 0,1++	0,16	+ 40 + +	+ +50 +	400
DN50	+ + + + + + + + + + + + + + + + + + + +	0,1	0,16	40	50	400
		0,1575	0,252	63	78,75	
DN65	+ + 2+ +	0,1575	0,25	63	78,75	400
		0,25	0,4	100	125	
	1, 1,	0,4	0,64	100	125	250
DN80	+ + 2+ + + + + +	0,25	0,4	100	125	400
		0,4	0,64	160	200	
	+ + + + + +	0,625	+ + 1+ +	+ 100+ +	+ +125 +	160
		0,64	+ +1,02 +	+ 160+ +	+ -200 +	+ 250 -
DN100	+ + + + + + + + + + + + + + + + + + + +	+ 0,4++	0,64	+ 160+ +	+ +200 +	400
		0,625	+ + 1+ +	250+	312,5	
	+ + + + + + + + + + + + + + + + + + + +	+ + + +	⁺ ⁺ 1,6 ⁺	160	200	160
		+ + + +	1,6	250	312,5	250
DN125	+ + 2+ +	0,625	1 1 1	250	312,5	400
		1	1,6	400	500	
	+ + 1+ + +	1,56	2,5	250	312,5	160
		1,6	2,56	400	500	250
DN150	+ + 2+ + + + + + + + + + + + + + + + +	+ + + +	+ +1,6 +	400	500	400
		+1,575 +	+ 2,52 +	+ 630+ +	+ 787,5 +	
	+ + + + + + + + + + + + + + + + + + + +	+ 2,5++	+ + 4+ +	+ 400+ +	+ +500 +	+160
		2,52	4,03	+ 630+ +	+ 787,5 +	250
DN200	+ + 2+ +	1,575	2,52	+ 630+ +	⁺ 787,5 ⁺	400
	+ + 1+ +	3,94	6,3	630	787,5	160
DNOTO	2	2,5	4	1000	1250	400
DN250	1 1 1	6,25	10	1000	1250	160
DNIZOO	2	4	6,4	1600	2000	400
DN300	+ + 1+ +	10	16	1600	2000	160
DN350	1 or 2	15,625	25	2500	3125	160
DN400	+ 1 or 2 +	+ 25 + +	+ +40 +	4000	+ 5000 +	+160
DN450	1 or 2	+ 25 + +	+ +40 +	4000 +	+ 5000 +	+ 160
DN500	1 or 2	39,375	+ +63- +	+ 6300 +	+ 7875 +	+ 160
DN600	1 or 2	+ 63 + +	100,8	6300	+ 7875 + ·	100



OIML Member StateThe Netherlands

Number R49-1/2006-NL1-12.01 revision 9 Project number SO16202611 Page 4 of 5

Meter size	Indicating range [m³]	Verification scale interval [m³]
DN25, DN40 and DN50	99.999.999	+ + + + 0,0001+ + + +
DN65, DN80, DN100, DN125 and DN150	99.999.999	0,001
DN200, DN250, DN300, DN350, DN400 and DN450	99.999.999	0,01
DN500 and DN600	99.999.999	+ + + + + + + + + + + + + + + + + + + +

Production location

The water meter is produced at one of the following production locations:

- KROHNE Altometer
 Kerkeplaat 12
 3313 LC Dordrecht
 The Netherlands
- KROHNE Measurement Technology (Shanghai) Co., Ltd. No. 555 Minshen Road, Songjiang Industrial Zone Shanghai 201612 China

01



OIML Member State The Netherlands

Number R49-1/2006-NL1-12.01 revision 9 Project number SO16202611 Page 5 of 5

Revision History

This revision replaces the previous versions.

Revision	Date + + + + +	Changes + + + + + + + + + + + + + + + + + + +
Initial	28 March 2012	
1 + + +	22 October 2012	New software version added
2 + + +	16 April 2013	New software version added
3 + + +	26 September 2014	New software version added
4 + + +	18 March 2015	Added sizes + + + + + + + + + + + + + + + + + + +
5 + + +	21 April 2015	New software version added
6 + + +	13 July 2015	New software version added
7 + + + + +	30 March 2016 + +	New electronics, software version and optional power supply added + + + + + + + + + + + + + + + + + +
8	16 June 2016	New software version added
9 + + +	14 July 2016	New software version added