

Member State of OIML  
United Kingdom of Great Britain  
and Northern Ireland

OIML Certificate No  
R51/2006-GB1-12.01  
Revision 1

## OIML CERTIFICATE OF CONFORMITY

Issuing authority: **National Measurement Office**  
Person responsible: **Paul Dixon – Director, Product Certification**  
Applicant: **Digi Europe Ltd  
Digi House  
Rookwood Way  
Haverhill  
Suffolk, CB9 8DG  
United Kingdom**  
Manufacturer: **The applicant**  
Identification of the  
certified pattern: **LI-700E / CWL-700E**

This certificate attests the conformity of the above-mentioned pattern (represented by the samples identified in the associated test report) with the requirements of the following Recommendation of the International Organisation of Legal Metrology (OIML):

### **OIML R 51 - Edition 2006(E) for accuracy classes Y(a) and XIII(1)**

This certificate relates only to the metrological and technical characteristics of the pattern of the instrument concerned, as covered by the relevant OIML International Recommendation.

This certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the certificates reference number and the name of the OIML Member State in which the certificate was issued, partial quotation of the certificate or of the associated test report is not permitted, though they may be reproduced in full.

This revision replaces previous versions of the certificate.

**Issue Date:** 16 February 2015  
**Reference No:** TS0101/0016



**Signatory: G Stones**  
**for Chief Executive**



The conformity was established by tests and examination described in the associated pattern evaluation report P00907/1 which includes 23 pages.

**Characteristics of the instrument:**

This pattern of an automatic catchweigher, designated the LI-700E, operates as an automatic weight or weight/price labeller (Category Y) and as an automatic checkweigher (category X). The instrument is designated the CWL-700E when configured to operate only as an automatic checkweigher (category X).

The instrument comprises a self-indicating and price-computing weighing machine with associated thermal label printer and mechanical handling facilities. It is designed to weigh packs statically, at a constant rate of operation.

Construction:

- Stainless steel frame
- Scale conveyor, optional in-feed and out-feed conveyors (any number)
- Labeller
- Control cabinet located behind the conveyors, comprising:
  - o Apex Technology combined PC and LCD display type AHM-6127A
  - o Teraoka TPB-03484 A/D converter
  - o TDK Lambda power supply unit type LS75 and UPS backup type Pico UPS-100

Devices:

- Initial zero-setting device ( $\leq 4\%$  of Max)
- Semi-automatic zero-setting device ( $\leq 4\%$  of Max)
- Automatic zero-setting after time interval ( $\leq 107$  min)
- Zero-tracking device
- Preset tare device
- Semi-automatic tare device (subtractive)
- Zero indication
- Calibration not accessible to user
- Price computation
- PLUs

Technical data:

Maximum capacity (Max)	3 kg	6 kg	10 kg
Scale interval (e =)	2 g		5 g
Minimum capacity (Min)	20 e		
Tare (T)	$\leq - 50\%$ Max		
Load cell E <sub>max</sub>	15 kg	20 kg	
Maximum operating rate	$\leq 45$ packs/min		
Maximum conveyor speed	$\leq 40.0$ m/min		
Climatic environment	0 to 40 °C Non-condensing (closed)		
Electromagnetic environments	E1 and E2		
Power supply	100-240 V a.c. / 50-60 Hz single phase		
Label applicator pneumatic pressure	4-6 bars		
Accuracy class	Y(a) and XIII(1)		

Load cell:

The load cell is an HBM SP4M C3MR.

Software:

The software version number is 2.xx.xx.xxxx which is displayed during the power-up sequence of the instrument.

Alternatively, the instrument may use the World View software.

The legally relevant software is contained within two dll files, identified as follows in the “About” screen:

HeaderDisplay.dll	Version 1.0.0.10
HI710.dll	Version 1.0.0.79

Interfaces:

- Ethernet
- USB

Alternatives:

Max and e may differ from the values specified in the table on page 2 provided a compatibility of modules is established, based on the following technical data

Maximum number of scale intervals	6,000
Load cell excitation voltage	3.3 Vdc
Minimum load cell impedance	43 $\Omega$
Maximum load cell impedance	1100 $\Omega$
Minimum input voltage per verification scale interval	0.88 $\mu$ V
Measuring range minimum voltage	0 mV
Measuring range maximum voltage	40 mV
Fraction of maximum permissible error	$P_{ind} = 0.5$
Load cell cable (from indicator to load cell junction box)	Maximum length = 1.5 m

Any compatible load cell(s) may be used providing the following conditions are met:

- There is a respective OIML Certificate of Conformity (R60) issued for the load cell.
- The certificate contains the load cell types and the necessary load cell data required for the manufacturer’s declaration of compatibility of modules, and any particular installation requirements. A load cell marked NH is allowed only if humidity testing to R76 has been conducted on this load cell.
- The compatibility of the load cells and indicator is established by the manufacturer by means of the compatibility of modules calculation at the time of verification.
- The load cell transmission conforms to a standard type.

**Certificate History**

<b>ISSUE NO.</b>	<b>DATE</b>	<b>DESCRIPTION</b>
R51/2006-GB1-12.01	08 August 2012	Certificate first issued
R51/2006-GB1-12.01 rev 1	16 February 2015	World View software added.