

OIML Member State
The Netherlands

Number R51/2006-NL1-12.04
Project number 12200524
Page 1 of 2

Issuing authority	NMi Certin B.V. Person responsible: C. Oosterman
Applicant	Teraoka Seiko Co. Ltd. 13-12 Kugahara, 5-Chome Ohta-Ku, Tokyo 146-8580 Japan
Manufacturer	Teraoka Seiko Co. Ltd. 13-12 Kugahara, 5-Chome Ohta-Ku, Tokyo 146-8580 Japan
Identification of the certified type	An Automatic catchweighing instrument Type : AW-4600CPR-..., or AW-4600...
Characteristics	See next page

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R51 - Edition 2006 (E) for accuracy class Y(a)

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified.
This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority **NMi Certin B.V., OIML Issuing Authority NL1**
21 December 2012

C. Oosterman
Head Certification Board

NMi Certin B.V.
Hugo de Grootplein 1
3314 EG Dordrecht
the Netherlands
T +31 78 6332332
certin@nmi.nl
www.nmi.nl

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

Parties concerned can lodge objection against this decision, within six weeks after the date of submission, to the general manager of NMI (see www.nmi.nl).

The conformity was established by the results of tests and examinations provided in the associated OIML Test Report(s):

- No. NMI-12200524-01 dated 5 December 2012 that includes 9 pages;
- No. NMI-12200524-02 dated 7 December 2012 that includes 13 pages.

Characteristics of the automatic catchweighing instrument

Destined to be used as	weigh price labeler (with or without lever works)	
Accuracy class	Y(a) The actual accuracy class shall be determined at initial verification	
Max	$6 \text{ kg} \leq \text{Max} \leq 15 \text{ kg}$	
Min	$\geq 20 \text{ e}$ for class Y(a)	
Verification scale interval	$e \geq 1 \text{ g}$	
Maximum number of scale intervals	$n \leq 3000$ divisions per partial weighing range.	
Maximum partial weighing ranges	2	
Tare	$T \leq -\text{Max}_1$	
Maximum weighing speed	30 packages per minute (AW-4600CPR-...) 36 packages per minute (AW-4600...)	
Temperature range	-10 °C / +40 °C	
Environment classes	E2	
Power supply voltage	200 – 240 V AC, 50/60 Hz	
Software identification Application software		
Filename	Checksum	Remarks
scale.o	DCB3B455, 4CB0B455, A2008463 or 49EB22FC	-
Software identification Firmware A/D board		
A/D board	Software version	Remarks
TPB-2786	1.xx	xx is a number between 00 and 99 representing minor version numbers which contain improvements or bug fixes not under legal control
TPB-3356	3.xx	