

# OIML CERTIFICATE OF CONFORMITY

| To Beijing True-Tec Co.,Ltd  |                               |
|------------------------------|-------------------------------|
| This certificate attests the | conformity of the type of the |
| Load Cell PA06               | with the requirements         |
| of the Recommendation        | R60(2000) of the              |
| International Organization o | f Legal Metrology(OIML).      |



The CIML member



## OIML CERTIFICATE OF CONFORMITY

#### Issuing authority

Name: Office of OlML Affairs, General Administration of Quality Supervision, Inspection and Quarantine

Address: N0.9 Madiandonglu, Haidian District, Beijing, 100088 China

#### Applicant

🐪 Name:

Beijing True-Tec Co.,Ltd

Address:

, Room B#-303, No.10A, Long Qing Street, BDA, Beijing 100176 China

Manufacturer of the certified type (if the manufacturer is not the applicant)

Name:

Address:

### Identification of the certified type

Load Cell

| Model designation  | PA06      |      |      |      |      |      |      |      |      |      |  |  |
|--|-----------|------|------|------|------|------|------|------|------|------|--|--|
| Accuracy class   | C4        |      |      |      |      |      |      |      |      |      |  |  |
| Maximum capacity(Emax)                                   | 3kg       | 5kg  | 7kg  | 10kg | 15kg | 20kg | 30kg | 35kg | 50kg | 75kg |  |  |
| Minimum load cell<br>verification interval (Vmin)        | 0.7g      | 1.2g | 1.6g | 2.5g | 3.5g | 5g   | 7g   | 8g   | 15g  | 25g  |  |  |
| Minimum dead load (Emin)                                 | 0         |      |      |      |      |      |      |      |      |      |  |  |
| Maximum number of load cell interval (n <sub>max</sub> ) | 4000      |      |      |      |      |      |      |      |      |      |  |  |
| Apportionment factor (Psc)                               | 0.7       |      |      |      |      |      |      |      |      |      |  |  |
| Safe overload  | 150% Emax |      |      |      |      |      |      |      |      |      |  |  |
| Operating Temperature range                              | -10°C40°C |      |      |      |      |      |      |      |      |      |  |  |
| Humidity condition                                       |           |      |      |      |      |      |      |      |      |      |  |  |

The numbers of the associated test reports and the included pages:

LXfc2005-6003 18 pages, LXfc2005-6004 17 pages

This certificate attests the conformity of the above-mentioned type(represented by the samples identified in the associated test report) with the requirements of the following Recommendation(s) of the International Organization of Legal Metrology (OIML).

R:

60

Edition:

2000

For accuracy class (if applicable):

This certificate relates only to the metrological and technical characteristics of the type of the instrument concerned, as covered by the relevant OIML International Recommendation(s). This certificate does not bestow any form of legal international approval. The conformity was established by tests described in the associated test reports.

The CIML member



Important note: Apart from the mention of the certificate's reference number and the name of the OIML Member State in which the certificate was issued, partial quotation of the certificate or of the associated test report is not permitted, though they may be reproduced in full.