





Member State of OIML Japan

## OIML CERTIFICATE OF CONFORMITY

Issuing authority

Name:

National Metrology Institute of Japan / National Institute of

Advanced Industrial Science and Technology (NMIJ / AIST)

Address:

AIST Tsukuba Central 3-9, Tsukuba Ibaraki 305-8563, Japan

Person responsible:

Dr. Tamotsu Nomakuchi, President of AIST

Applicant

Name:

YAMATO SCALE CO., LTD.

Address:

5-22, Saenba-cho, Akashi, Hyogo, 673-8688, Japan

Manufacturer of the certified pattern

Name:

YAMATO SCALE CO., LTD.

Address:

5-22, Saenba-cho, Akashi, Hyogo, 673-8688, Japan

Identification of the certified pattern:

Compression load cell

Type:

DCC11-20T, DCC11-24T, DCC11-36T

Fraction:

Pi=0.7

Temperature range

-10 °C / 40 °C







Member State of OIML Japan

OIML Certificate No. R60/2000-JP1-11.06

## Characteristics:

| Model designation                                       |                  |        | DCC11-20T                             | DCC11-24T | DCC11-36T |
|---|------------------|--------|---------------------------------------|-----------|-----------|
| Model designation                                       | Class            |        | DCC11-201                             | C         | DCC11-301 |
| Accuracy class  | Class            | -      |                                       |           |           |
| Maximum number of load cell verification intervals      | n <sub>max</sub> | -      | 6000<br>5000                          |           |           |
|   |                  |        | 4000                                  |           |           |
|   |                  |        | , , , ,                               |           |           |
|   |                  |        | 3000                                  |           |           |
| Humidity symbol   |                  |        | СН                                    |           |           |
| Minimum dead load                                       | $E_{min}$        | kg     | 0                                     |           |           |
| Maximum capacity  | $E_{\rm max}$    | kg     | 20,000                                | 24,000    | 36,000    |
| Safe load limit   | $E_{ m lim}$     | kg     | 30,000                                | 36,000    | 54,000    |
| Minimum verification interval                           | v <sub>min</sub> | kg     | 1.666                                 | 2         | 3         |
|   |                  |        | 2                                     | 2.4       | 3.6       |
|   |                  |        | 2                                     | 2.4       | 3.6       |
|   |                  |        | 2                                     | 2.4       | 3.6       |
| Apportionment factor                                    | $p_{ m LC}$      |        | 0.7                                   |           |           |
| Ratio of minimum LC Verification interval Y=Emax / vmin | Y                | -<br>- | 12000                                 |           |           |
|   |                  |        | 10000                                 |           |           |
|   |                  |        | 10000                                 |           |           |
|   |                  |        |                                       | 10000     |           |
| Ratio of minimum dead                                   |                  |        |                                       | 6000      |           |
| load output return                                      | Z                | -      | in the case of $n_{\text{max}}$ =6000 |           |           |
| $Z=E\max/(2*DR)$  |                  |        |                                       |           |           |
| Excitation voltage                                      |                  | V DC   | 8 ~ 15                                |           |           |
| Cable length  |                  | m      | 20                                    |           |           |
| (maximum)   |                  | m      |                                       |           |           |

This certificate attests the conformity of the above-mentioned pattern (represented by the samples identified in the associated test report(s) with the requirements of the following Recommendation of the International Organization of Legal Metrology - OIML):

R60, edition 2000 (E)


For accuracy class C

This certificate relates only to the metrological and technical characteristics of the pattern of the instrument concerned, as covered by the relevant OIML International Recommendation.

This certificate does not bestow any form of legal international approval.

The conformity was established by tests described in the associated test report no. 11-07/R60:2000, that includes 33 pages.









The Issuing Authority NMIJ/AIST

部位別が同日 一般ではアンター ではアンター 日本記書記書

Dr. T. Nomakuch即量事制 President of AIST 2011-08-09 The CIML member

Dr. Y. Miki

2011-08-09

Important note: Apart from the mention of certificate's reference number and the name of the OIML Member State in which the certificate was issued, partial quotation of the certificate or the associated test report is not permitted, though they may be reproduced in full.