

OIML Certificate of Conformity

OIML Member State The Netherlands Number R60/2000-NL1-11.07 Project number 11200201 Page 1 of 3

Issuing authority NMi Certin B.V. Person responsible: C. Oosterman Applicant Tedea-Huntleigh or Vishay Precision 2 Haofan St., Holon, Israel Tedea-Huntleigh or Vishay Precision Manufacturer 2 Haofan St., Holon, Israel Identification of the A bending beam Load Cell certified type Type Characteristics See next page This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML): OIML R60 - Edition 2000 (E) for accuracy class C This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval. Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full. NMi Certin B.V., Issuina OIML Issuina 13 April 2011 Oosterman Head Certification Boar NMi Certin B V This document is issued under the Parties concerned can Hugo de Grootplein 1 provision that no liability is lodge objection against 3314 EG Dordrecht accepted and that the applicant this decision, within six shall indemnify third-party liability. the Netherlands weeks after the date of T+31 78 6332332 submission, to the The notification of NMi Certin B.V. certin@nmi.nl general manager of NM as Issuing Authority can be verified www.nmi.nl (see www.nmi.nl). at www.oiml.org



OIML Certificate of Conformity

OIML Member State The Netherlands Number R60/2000-NL1-11.07 Project number 11200201 Page 2 of 3

- NO. NM-11200201-0	05 dated 15 April 1 dated 13 April 2															
Characteristics of the	Load Cell:															
Туре	* * * * * *	1242														
Fraction P _i	* * * * * *	0,7														
Maximum capacity	+ + E _{max} + + +	50 kg up to and including 250 kg														
Humidity Class	+ + + + + + + + + + + + + + + + + + +	CH -10 °C / +40 °C C														
Temperature range	* * * * * *															
Accuracy Class	* * * * * *															
Maximum number of loa cell verification intervals	n	1000	1000 2000 3000 4000 50													
Ratio of minimum LC verification interval	Y = E _{max} / v _{min}	· + + + + + + + + + + + + + + + + + + +	20000													
Ratio of minimum dead output return	load Z = E _{max} /2*DR	· + + + + · + + + +	+ + + + + + + + + + + + + + + + + + + +	+ + + + 000 + + + +	· + + + + · · · · · · · · · · · · · · ·											
* * * * * * * *	+ + + + + +	* * * * *	+ + + + + +	+ + + + +	• • • • • •											



OIML Certificate of Conformity

OIML Member State The Netherlands Number R60/2000-NL1-11.07 Project number 11200201 Page 3 of 3

Туре	+ +	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	124	12	+	+	+	+ +		• +	+	+
Fractic	on P _i	+++++++++++++++++++++++++++++++++++++++	* +	+++++++++++++++++++++++++++++++++++++++	+++++	++++	++++	+ +	++++	+++++++++++++++++++++++++++++++++++++++	++++	+++++++++++++++++++++++++++++++++++++++	+ +	+++++++++++++++++++++++++++++++++++++++	+++++++++++++++++++++++++++++++++++++++	+++++++++++++++++++++++++++++++++++++++	+ +	+ +	+ +	+ +	0,7	7	+ +	+ +	+ +	+ + + +	• •	• +	+++++++++++++++++++++++++++++++++++++++	+++++++++++++++++++++++++++++++++++++++
Maxim	ium ca	apa	city	t	t	t	+	E _{ma}	x	ŧ	ŧ	ŧ	+	÷	t	+ 3	00	up	to a	and	d in	clu	din	ıg 5	00	kg	•	+	ŧ	+
Humic	lity Cl	ass	+	+	+	÷	+	+	÷	÷	+	÷	+	+	÷	÷	+	+	+	+	Cŀ	4	+	+	÷	+ +	- +	+	+	+
Tempe	eratur	e ra	nge	2 -	+++++++++++++++++++++++++++++++++++++++	+++++++++++++++++++++++++++++++++++++++	++++	+++++++++++++++++++++++++++++++++++++++	++++	+++++++++++++++++++++++++++++++++++++++	+ +	+++++++++++++++++++++++++++++++++++++++	++++	++++	+++++++++++++++++++++++++++++++++++++++	+++++++++++++++++++++++++++++++++++++++	+ +	+ +	- 1	0 °	c/.	+4(o °C	+++++++++++++++++++++++++++++++++++++++	+ +	+ + + +	н н н н	· + · +	++	+++++++++++++++++++++++++++++++++++++++
Accura	icy Cla	ss	1	÷	÷	+	+	t	+ 1	t	+	t	1	+	t	t	<u>+</u>	+	• • • • • • • • • • •						<u>+</u>	+ +	• •	: +	1	+
Maxim cell ve						d	+++	n _{max} + + +			1000		0	2000			300		00		+4	4000		+	500)	6	5000)	
Ratio o verific					+++	+++		Y = E _{ma}		+ / _{min}	+ + +	+++	+ + +	+ + +	++++	++++	+ + +	+ + +	+ + +	+ + +	700	00	+ + +	+ + +	+ +	+ + + +	• •	· + · +	+++	+++
Ratio o outpu			um	dea	ad I	oa		Z = E _{ma}		*DI	+ R +	+ + +	+ + +	+ + +	+ + +	+ + +	+ + +	+ + +	+ + + +	+ + + +	+ 800	+ 00 +	+ + +	+ + +	+ + +	* * *	* * *	· + · +	+ + +	+ + +
The ch	aracte	erist	tics	for	n _m	ax d	anc	Y	and	d Z	car	n be	e re	du	ced	se	par	ate	ly.	+	÷.	+	÷.	+	+	+ +	• •	: +	+	+