

OIML Certificate of Conformity

OIML Member State The Netherlands Number R60/2000-NL1-11.13 Project number 10200816 Page 1 of 2

NMi Certin B.V. Issuing authority Person responsible: C. Oostermar Applicant **G&P LIDÉN WEIGHING AB** Bilgatan 15 S-442 40 KUNGÄLV Sweden Manufacturer **G&P LIDÉN WEIGHING AB** Bilgatan 15 S-442 40 KUNGÄLV Sweden Identification of the A shear beam Load Cell certified type Type Characteristics See next page This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML): OIML R60 - Edition 2000 (E) for accuracy class C This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval. Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full. NMi Certin B.V., Issuing Authority **OIML Issuing Authority** 17 May 2011 Coosterman Head Certification Board NMi Certin B.V. This document is issued under the Parties concerned can Hugo de Grootplein 1 provision that no liability is lodge objection against 3314 EG Dordrecht accepted and that the applicant this decision, within six the Netherlands shall indemnify third-party liability. weeks after the date of T +31 78 6332332 submission, to the NSPECTION The notification of NMi Certin B.V. certin@nmi.nl general manager of NMi www.nmi.nl as Issuing Authority can be verified (see www.nmi.nl). Rva I at www.oiml.org



OIML Certificate of Conformity

OIML Member State The Netherlands Number R60/2000-NL1-11.13 Project number 10200816 Page 2 of 2

			orm t Re	-			sta	blis	hec +	d-by +	/ th +	ie r	esu	ts +	0† +	tes +	ts a	nd +	exa +	amı +	nat +	tior	is p	rov +	/ide +	d I	n ti	ne a	asso +	жіа +	atec	+	
	No	. N	Mi	102	200)81	6-0	1 d	ate	d 1	7 N	1ay	20	11	tha	it ir	nclu	Ides	31	pa	ige	s.											
Cha	ara	cte	ris	tic	s o	f tl	he	Loa	ad	Cel	I.																						
Fraction P_i Maximum capacity (E_{max}) Humidity Class Femperature range Accuracy Class Maximum number of load cell intervals (n) Ratio of minimum LC Verification interval $f = E_{max} / V_{min}$											+ + + + + + + + +	 : 0,7 : 450 kg up to and including 2250 kg : CH : -10 °C / +40 °C : C : 3000 : 10000 																					
at	io d	of r	nin	imu		de	ad	loa	d o	utp	ut	ret	urn	+	: *3	000) †																
=	E _{ma}	_{ax} /	(2 *	DI	۲)																												