

OIML Certificate of Conformity

OIML Member State The Netherlands Number R60/2000-NL1-11.22 Project number 11200444 Page 1 of 2

lssuing authority	NMi Certin B.V. Person responsible: C. Oos	terman		
Applicant	Zhonghang Electronic Mea Xinyuan Rd. North Zone o			+ + + + + + + na + + + + + + +
Manufacturer	Zhonghang Electronic Mea Xinyuan Rd. North Zone o			na
Identification of the certified type	A single point Load Cell Type	tinger L6Q∹	xx-xxx-xx series	
Characteristics	See next page			
identified in the OIML	the conformity of the above Test Report) with the requir tion of Legal Metrology (OI	rements of the follow		
	OIML R60 - Edition 2000 (E) for accuracy class	C + + + + +	
+ instrument covered by	only to the metrological and the relevant OIML Internati ot bestow any form of legal	onal Recommendati	on above-identifie	
OIML Member State in	from the mention of the Ce which the Certificate was is est Report(s) is not permittee	sued, partial quotat	ion of the Certifica	ite and of
* * * * * * * * *				
Issuing Authority	NMi Certin B.V., OIML Is 24 August 2011	suing Authority N	L1 + + + + +	
	24 August 2011			
	C. Oosterman			
	Head Certification Board			
NMi Certin B.V. Hugo de Grootplein 1 3314 EG Dordrecht the Netherlands T +31 78 6332332 certin@nmi.nl	This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability. The notification of NMi Certin B.V.	Parties concerned can lodge objection against this decision, within six weeks after the date of submission, to the general manager of NMi	AUTOM MOINL MAN	EXECTION
www.nmi.nl	as Issuing Authority can be verified at www.oiml.org	(see www.nmi.nl).	T REPTANCE ARRAS	RvA 122



OIML Certificate of Conformity

OIML Member State The Netherlands Number R60/2000-NL1-11.22 Project number 11200444 Page 2 of 2

he co DIML			-			stal +	blis	heo +	yd by	y th	ne r	esu	lts +	of 1	test +	ts a	nd	exa +	ami +	nat +	tior +	is p	rov +	ide +	d ii	n tł	ne a	35SC +	ocia +	ted	+		
No	o. N	Mi-	112	200	444	4-06	6 d	ate	d 2	4 A	ug	ust	20	11	tha	t in	clu	des	31	pa	ge	5.											
hara	cte	rist	tics	o	ftł	ne	Loa	ad	Cel	I:																							
Fraction P _i Maximum capacity (E_{max}) Humidity Class Temperature range Accuracy Class Maximum number of load cell intervals (n) Ratio of minimum LC Verification interval Y = E_{max} / V_{min} Ratio of minimum dead load output return									: 1 : C : - : 5 : 2	0,7 100 kg up to and including 500 kg CH -10 °C / +40 °C C 5000 20000																							
Ratio Z = E _m					dea	ad I	loa	d o	utp	out	ret	urn	+	: 5	000) +																	
+ +	+			÷																													