

OIML Certificate of Conformity

OIML Member State The Netherlands Number R60/2000-NL1-12.06 Project number 11200809 Page 1 of 2

lssuing authority	NMi Certin B.V. Person responsible: C. Oosterman	
Applicant	Keli Sensing Technology (Ningbo) Co., Ltd. No. 199 Changxing Road, Jiangbei District, Ningbo, China	
Manufacturer	Keli Sensing Technology (Ningbo) Co., Ltd. No. 199 Changxing Road, Jiangbei District, Ningbo, China	
Identification of the certified type	A shear beam Load Cell Type : SBO	
Characteristics	See next page	
identified in the OIML	the conformity of the above identified Type (represented by the sample(s) Test Report) with the requirements of the following Recommendation of the tion of Legal Metrology (OIML):	
	OIML R60 - Edition 2000 (E) for accuracy class C	
+ instrument covered by	only to the metrological and technical characteristics of the type of measuring the relevant OIML International Recommendation above-identified. ot bestow any form of legal international approval.	
OIML Member State in	from the mention of the Certificate's reference number and the name of the which the Certificate was issued, partial quotation of the Certificate and of est Report(s) is not permitted, although either may be reproduced in full.	
Issuing Authority	NMi Certin B.V., OIML Issuing Authority NL1 10 April 2012	
	C. Oosterman Head Certification Board	
NMi Certin B.V. Hugo de Grootplein 1 3314 EG Dordrecht the Netherlands T +31 78 6332332 certin@nmi.nl www.nmi.nl	This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability. The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org	



OIML Certificate of Conformity

OIML Member State The Netherlands Number R60/2000-NL1-12.06 Project number 11200809 Page 2 of 2

DIML	. T	est	: Re	epo	ort(s):																										
Ņ	о.	N	Mi	11	200	080	9-0	4 d	ate	d 1	0 A	pri	1 20)12	th	at i	nclı	ude	s 2	7 p	age	es.										
Char	ac	te	ris	tic	s o	ftl	he	Loa	ad (Cel	Ľ																					
Fraction P _i Maximum capacity (E _{max}) Humidity Class Temperature range Accuracy Class Maximum number of load cell intervals (n) Ratio of minimum LC Verification interval Y = E _{max} / V _{min}														: 6 : C : - : 3 : 1	0,7 600 kg up to and including 3000 kg CH -10 °C / +40 °C C 3000 10000																	
	aximum capacity (E _{max}) umidity Class emperature range ccuracy Class aximum number of load cell interval atio of minimum LC Verification inter												urr	+	: 3	000)															
F +	IIax	÷	÷		+																											