

## OIML Certificate of Conformity

**OIML Member State** The Netherlands Number R60/2000-NL1-12.07 Project number 11200809 Page 1 of 2

Issuing authority	NMi Certin B.V. Person responsible: C. Oost	erman + + + + +		
Applicant	Keli Sensing Technology (N No. 199 Changxing Road, J		bo, China	
Manufacturer	Keli Sensing Technology (N No. 199 Changxing Road, J		bo, China	
Identification of the certified type	A shear beam <b>Load Cell</b> Type	+ + + + + + + + + + + + + + + + + + +		
Characteristics	See next page			
identified in the OIML	the conformity of the above Test Report) with the require tion of Legal Metrology (OIN	ements of the followi		
	OIML R60 - Edition 2000 (E	) for accuracy class C		
+ instrument covered by	only to the metrological and the relevant OIML Internatic ot bestow any form of legal i	onal Recommendation	n above-identifie	
OIML Member State in	from the mention of the Cer which the Certificate was iss est Report(s) is not permitted,	ued, partial quotatio	n of the Certifica	te and of
Issuing Authority	NMi Certin B.V., OIML Is	uing Authority NL	+ + + + +	
	10 April 2012			
	C. Oosterman			
	Head Certification Board			
NMi Certin B.V. Hugo de Grootplein 1 3314 EG Dordrecht the Netherlands T +31 78 6332332 certin@nmi.nl www.nmi.nl	This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability. The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org	Parties concerned can lodge objection against this decision, within six weeks after the date of submission, to the general manager of NMi (see www.nmi.nl).	OIML PROIML CEATANCE ARRAN	INSPECTION RVA   122



## OIML Certificate of Conformity

**OIML Member State** The Netherlands Number R60/2000-NL1-12.07 Project number 11200809 Page 2 of 2

<ul> <li>No. R60/2000-NL1-06.03 dated 22 February</li> <li>No. NMi-11200809-05 dated 10 April 2012</li> <li>Characteristics of the Load Cell:</li> </ul>																																
	action P <sub>i</sub> aximum capacity (E <sub>max</sub> )									: 0,7 : 150 kg up to and including 750 kg 1 t up to and including 5 t																						
lu	mic	lity	Cla	iss										1	: 0	Ή						1										
	-		ture		ng	e								÷	100	10 °	°C /	+4(	) °C	-												
			Cla า ทเ			df		d c	The	int	on		(n)	+	: C		+															
			nin											+		000																
			V <sub>mi</sub>		+	+	+	+	+	+	+	+	+	+	+	+	+															
			nin			dea	ad	loa	d o	utp	out	ret	urn	+ :	3	000	) +															
=	Em	<sub>ax</sub> /	(2 *	D	<b>(</b> )																											