

## OIML Certificate of Conformity

**OIML Member State** The Netherlands Number R60/2000-NL1-12.44 Project number 12200198 Page 1 of 2

+ Issuing authority	NMi Certin B.V.
Applicant	SEWHACNM Co., Ltd. #302/303 102Dong, Bucheon Techno Park Ssangyong 3rd, 36-1, Samjeong- Dong, Ojeong-Gu, , Bucheon City, GyungGi-Do, Korea
Manufacturer	SEWHACNM Co., Ltd. #302/303 102Dong, Bucheon Techno Park Ssangyong 3rd, 36-1, Samjeong- Dong, Ojeong-Gu, , Bucheon City, GyungGi-Do, Korea
Identification of the certified type	A tension <b>load cell</b> Type : SS300
+ Characteristics + +	See next page + + + + + + + + + + + + + + + + + + +
<sup>+</sup> identified in the OIML	the conformity of the above identified Type (represented by the sample(s) Test Report) with the requirements of the following Recommendation of the tion of Legal Metrology (OIML):
	OIML R60 - Edition 2000 (E) for accuracy class C
instrument covered by This Certificate does no <i>Important note:</i> Apart OIML Member State in	only to the metrological and technical characteristics of the type of measuring the relevant OIML International Recommendation above-identified. of bestow any form of legal international approval. from the mention of the Certificate's reference number and the name of the which the Certificate was issued, partial quotation of the Certificate and of est Report(s) is not permitted, although either may be reproduced in full.
+ Issuing Authority	NMi Certin B.V., OIML Issuing Authority NL1
	13 September 2012
	C. Oosterman + + + + + + + + + + + + + + + + + + +
	Head Certification Board
NMi Certin B.V. Hugo de Grootplein 1 3314 EG Dordrecht the Netherlands T +31 78 6332332 certin@nmi.nl www.nmi.nl	This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability. The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org



## OIML Certificate of Conformity

**OIML Member State** The Netherlands Number R60/2000-NL1-12.44 Project number 12200198 Page 2 of 2

				Re Ni-				-01	da	ated	d 13	3 Se	ept	em	beı	· 20	)12	tha	nt ir	nclu	ıde	s 27	7 pa	ges.									
Cł	ha	rac	te	rist	ics	of	th	e l	oa	d c	ell:	+ + +																					
Fraction p <sub>LC</sub>										÷	÷	+	÷	÷	÷	÷	+ 0	7	+	+	÷	÷	+	+	+	-							
M	ax	im	um	cap	baci	ty (	(E <sub>m</sub>	ax)	÷.	*	<u>*</u>	<u>*</u>	<u>*</u>	1	+	1000 kg up to and including 5000 kg																	
Humidity Class							-	СН																									
Temperature range							-10 °C / +40 °C															-											
Accuracy Class							+	+ + + + + + + + C + + + + + + + +															-										
Μ	ах	im	um	nu	mb	er o	of I	oa	d c	elli	inte	erva	als	(n)	+	+	+	+	÷	+	+	+	30	00+	+	+	+	+	+	+	+	-	
Ratio of minimum LC Verification interval Y = $E_{max} / V_{min}$							++	+ +	+ +	+ +	+ +	+ +	+ +	+ +	60	00	+++	++++	+ +	+ +	+++	+ +	+++										
Ratio of minimum dead load output return Z = $E_{max}$ / (2 * DR)							+	+ +	++	+ +	+ +	++	+ +	++	30	00	++	+++	+	+ +	+++	++	++	-									
T٢	ne	cha	ara	cter	isti	cs f	or	n <sub>ma</sub>	<sub>ix</sub> a	nd	Υc	an	be	re	duc	ed	sep	ara	itel	y. Z	' is	pro	por	tion	al o	r ec	qua	l to	n,	nax•			
Ea	ach	р	od	uce	d lo	bad	ce	ell is	s su	ipp	lied	d w	ith	int	forr	nat	tior	n ab	oou	t its	s ch	nara	acte	ristic	s.								