





OIML Certificate Nº R76/1992-JP1-07.01

OIML Member State Japan

## OIML CERTIFICATE OF CONFORMITY

Issuing Authority

Name: National Metrology Institute of Japan /National Institute of

Advanced Industrial Science and Technology (NMIJ/AIST)

Address: AIST Tsukuba Central 3-9

Tsukuba Ibaraki 305-8563, Japan

Person responsible: Dr. Hiroyuki Yoshikawa, President of AIST

Applicant

Name: A&D Company, Limited

Address: 3-23-14, Higashi-ikebukuro, Toshima-ku, Tokyo 170-0013,

JAPAN

Manufacturer of the certified type

Name: Litra Co.,Ltd

Address: 7-5, Harajyuku, Hidaka-shi, Saitama 350-1205, JAPAN

Identification of the certified type:

Type AD-6121A

Further characteristics see page 2

This certificate attests the conformity of the above identified type (represented by the sample or samples identified in the associated Evaluation Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

R76-1, Edition 1992, including amendment1 (1994),

for accuracy class: III

This certificate relates only to the metrological and technical characteristics of the type of instrument covered by the relevant OIML Recommendation identified above.

This certificate does not bestow any form of legal international approval.







OIML Member State Japan OIML Certificate No R76/1992-JP1-07.01

The conformity was established by the results of tests and examinations provided in the associated Evaluation Report No R76/1992-JP1-07.01-ER.

The Issuing Authority

NMIJ/AIST

The CIML Member

Dr. H. Yoshikawa

President of AIST

2007-02-15

Dr. Y. Miki

2007-02-15

## Characteristics:

| Туре                          | AD-6121A        |
|-------------------------------|-----------------|
| Class                         |                 |
| Max =                         | 150 kg          |
| e =                           | 0.1 kg          |
| n=                            | 1500            |
| Min =                         | 2 kg            |
| Maximum Tare-balancing effect | T = - 150 kg    |
| Temperature range             | + 5 °C /+ 35 °C |

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate is issued, partial quotation of the Certificate and of the associated Evaluation Report is not permitted, although either may be reproduced in full.