



OIML Member State

Denmark

OIML Certificate No. R76/2006-A-DK2-18.04 Rev. 1

OIML CERTIFICATE ISSUED UNDER SCHEME A

OIML Issuing Authority

Name: **FORCE Certification A/S**

Address: Park Allé 345, 2605 Brøndby, Denmark

Person responsible: Leif Madsen

Applicant

Name: Cardinal Scale Manufacturing Company.

Address: 203 East Daugherty Street,

Webb City, Missouri 64870

USA

Manufacturer The applicant

Identification of the certified type (the detailed characteristics will be defined in the additional pages)

185

Designation of the module (*if applicable*)

Non-automatic electronic weighing indicator

This OIML Certificate attests the conformity of the above identified type (represented by the sample(s) identified in the OIML type evaluation report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 76-1, Edition (year): 2006

For accuracy class (if applicable): III or IIII

OIML Certificate No. R76/2006-A-DK2-18.04 rev.1

This OIML Certificate relates only to metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML Recommendation identified above.

This OIML Certificate does not be tow any form of legal international approval.

The conformity was established by the results of tests and examinations provided in the associated OIML type examination and evaluation reports:

No. 117-34433.10, dated 25 July 2018 that includes 69 pages

No. 117-34433.90, dated 01 October 2018 that includes 3 pages

No. 117-35298.10, dated 20 November 2018 that includes 19 pages

No. 117-35298.90, dated 20 November 2018 that includes 3 pages

The technical documentation relating to the identified type is contained in documentation file:

No. 117-34433.10 and 118-35298.10

OIML Certificate History

Revision No.	Date —	Description of the modification
First issuance	25 October 2018	/-
Revision 1	03 December 2018	Event counters device added.

Catic Identification, signature and stamp

The OIML Issuing Authority

FORCE Certification A/S

Date: 03 December 2018

Jens Hovgård Jensen

Certification Manager

Apart from the mention of the Certificate's reference number and the name of the Important note:

> OIML Member State in which the Certificate is issued, partial quotation of the Certificate and of the associated OIML type evaluation report(s) is not permitted,

although either may be reproduced in full.

Descriptive annex

Characteristics

Type: 185 Accuracy class: III

Weighing range: Single-interval

Maximum capacity (Max): $n \times e$ Verification scale interval (e =): Max / e

Maximum number of Verification

Scale Intervals (n): ≤ 6000 Maximum subtractive tare effect: -Max Fractional factor: p'i = 0.5Minimum input voltage per VSI: $1.2 \mu V$ Excitation voltage: 5 VDC Circuit for remote sense: present Minimum input impedance: 87 ohm Maximum input impedance: 1100 ohm

Mains power supply: 100-240 VAC, 50/60 Hz, using AC to 12V DC external

adapter.

Six (6) AA ordinary or rechargeable batteries supplying 9

VDC

Operational temperature: -10 °C to +40 °C

Maximum 6-wire cable length between

indicator and junction box: 858 m/mm²

Software

The legally relevant software has version 1.0.xx, where xx can be 04 to 99 reflecting non-legally relevant changes.

The software version is displayed as part of the power-up sequence.

'Cati

Interfaces

- RS232

Devices

- Initial zero setting device ($\leq 4\%$ of Max)
- Semi-automatic zero setting device ($\leq 4\%$ of Max)
- Zero tracking device ($\leq 4\%$ of Max)
- Semi-automatic subtractive tare device
- Gross / Net display
- Printing device
- Weighing unit toggling device
- Gravity compensation device
- Stable equilibrium, Zero AND Net indicators.
- Calibration event counter
- Configuration event counter