



OIML Certificate

OIML Member State
The Netherlands

Number R76/2006-A-NL1-19.35
Project number 2363100
Page 1 of 2

Issuing authority NMI Certin B.V.
Person responsible: C. Oosterman

Applicant and Manufacturer Goldcell (Malaysia) Sdn Bhd
T3A-20-17, Pusat Perdagangan Icon City,
Jalan SS 8/39, 47300 Petaling Jaya
Selangor
Malaysia

Identification of the certified type A **Indicator** or **Terminal**
Type : INS709

Characteristics See next page

This OIML Certificate is issued under scheme A.

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 76 - Edition 2006 for accuracy class **(III)** or **(III)**

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority **NMI Certin B.V., OIML Issuing Authority NL1**
4 July 2019


C. Oosterman
Head Certification Board

NMI Certin B.V.
Thijsseweg 11
2629 JA Delft
The Netherlands
T +31 88 6362332
certin@nmi.nl
www.nmi.nl

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMI Certin B.V. as Issuing Authority can be verified at www.oiml.org



The conformity was established by the results of tests and examinations provided in the associated OIML Test Report:

- No. NMI-11200809-07 dated 7 December 2012 that includes 26 pages.

Characteristics of the indicator:

Accuracy class	III or IIII
Fraction of the maximum permissible error	0,0
Weighing range	Single interval
Power supply voltage	110 – 240 V AC 50/60 Hz
Software identification	Version number: v0.1 or v0.2.