

**OIML Member State** 

The Netherlands

## **OIML** Certificate



Number R76/2006-A-NL1-20.09 Project number 2433988 Page 1 of 2

| Issuing authority                    | NMi Certin B.V.<br>Person responsible: M. Bou   | udewijns |    |                                 |
|--------------------------------------|---|----------|----|---------------------------------|
| Applicant and<br>Manufacturer        | Shanghai Teraoka Electror<br>No.6058 of Nan Ting Road<br>Ting Ling Town, Jin Shan E<br>Shanghai 201505<br>China |          | ł. |                                 |
| Identification of the certified type | A <b>Weighing module</b><br>Type  |          | :  | AD2000, RM-5800LL B, RM-5800NLL |
| Characteristics                      | See next page   |          |    |                                 |

This OIML Certificate is issued under scheme A.

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

**OIML R 76** - Edition 2006 for accuracy class (III)


This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

*Important note:* Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.





NMi Certin B.V. Thijsseweg 11 2629 JA Delft The Netherlands T +31 88 6362332 certin@nmi.nl www.nmi.nl



## **Certification Board**

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon at the top of the electronic version of this certificate.







\_

OIML Member State The Netherlands

## **OIML** Certificate



Number R76/2006-A-NL1-20.09 Project number 2433988 Page 2 of 2

The conformity was established by the results of tests and examinations provided in the associated OIML Test Report(s):

- No. NMi-14200679-01 dated 15 February 2015 that includes 43 pages;
- No. NMi-14200679-02 dated 15 February 2015 that includes 28 pages;
- No. NMi-15200365-01 dated 12 June 2015 that includes 15 pages;
- No. NMi-2353595-01 dated 8 May 2019 that includes 13 pages;
- No. NMi-2391421-01 dated 4 September 2019 that includes 14 pages;
- No. NMi-2433988-01 dated 10 March 2020 that includes 42 pages;
- No. NMi-2441754-01 dated 10 March 2020 that includes 26 pages.

## Characteristics of the non-automatic weighing instrument:

| Configuration   | Weighing module  |   |  |  |  |
|---|--|---|--|--|--|
| Accuracy class  |  |   |  |  |  |
| Maximum capacity  | 3 kg ≤ Max ≤ 37,5 kg   |   |  |  |  |
| Verification scale interval                               | e ≥ 1 g  |   |  |  |  |
| Weighing range(s)   | Single interval<br>Multi-interval  |   |  |  |  |
| Maximum number of scale intervals<br>(one weighing range) | n ≤ 3000   | n ≤ 7500                                    |  |  |  |
| Maximum number of scale intervals<br>(multi-interval)     | n ≤ 3000<br>(per partial weighing<br>range)  | n ≤ 7500<br>(per partial weighing<br>range) |  |  |  |
| Maximum number of<br>partial weighing ranges              | 2  |   |  |  |  |
| Fraction of the maximum permissible error                 | 1  |   |  |  |  |
| Tare  | $T \leq$ -50% for instruments with one weighing range $T \leq$ -Max_1 for multi-interval instruments |   |  |  |  |
| Temperature range   | -10 °C / +40 °C  |   |  |  |  |
| Power supply voltage                                      | For type AD2000:<br>12 V DC via RS232<br>For other types:<br>100 – 240 V AC 50/60Hz                  | For type AD2000:<br>5 V DC via USB          |  |  |  |
| Software identification                                   | Version number:  | Version number: 1.x.x (x= 09)               |  |  |  |