

OIML Member State
The Netherlands

Number R76/2006-A-NL1-20.21 revision 1
Project number 2512549
Page 1 of 3

Issuing authority NMI Certin B.V.
Person responsible: M. Boudewijns

Applicant and Manufacturer Mettler Toledo GmbH
Im Langacher 44
8606 Greifensee
Switzerland

Identification of the certified type An **Indicator / Terminal**
Type : IND890-1, IND930

Characteristics See next page

This OIML Certificate is issued under scheme A.

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 76 - Edition 2006 for accuracy class **II** or **III** or **III1**

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority

NMI Certin B.V., OIML Issuing Authority NL1
24 December 2020

Certification Board

NMI Certin B.V.
Thijsseweg 11
2629 JA Delft
The Netherlands
T +31 88 6362332
certin@nmi.nl
www.nmi.nl

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMI Certin B.V. as Issuing Authority can be verified at www.oiml.org

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon on top of the electronic version of this certificate.



The conformity was established by the results of tests and examinations provided in the associated OIML Reports:

Indicators:

- No. NMI-1900621-02 dated 24 May 2017 that includes 14 pages;
- No. NMI-1900621-03 dated 6 June 2017 that includes 26 pages;
- No. NMI-1901844-01 dated 28 May 2018 that includes 19 pages;
- No. NMI-2475906-01 dated 29 June 2020 that includes 26 pages;

Digital data processing devices:

- No. NMI-2373298-01 dated 16 December 2019 that includes 17 pages;
- No. NMI-2373298-02 dated 16 December 2019 that includes 15 pages;

Analog data processing devices:

- No. NMI-1900621-01 dated 24 May 2017 that includes 31 pages;
- No. NMI-2477319-01 dated 23 October 2020 that includes 21 pages.

Characteristics of the indicator / terminal:

Configuration		Digital load cell(s), weighing module or ADPD	
Accuracy class		II or III or IIII	
Weighing range(s)		Single interval Multi-interval Multiple range	
Load cell power supply		5 V DC / 12 V DC	
Fraction of the maximum permissible error		0	
Maximum number of load platforms		4	
Temperature range		-10 °C / +40 °C	
Power supply voltage		100 – 240 V AC 50/60 Hz	
Software identification	Software module	Version ⁽¹⁾	Unique ID
	Boot service 'Classic' version	V1.1.3 or v1.1.3	B645
	Scale server 'Classic' version	V1.y.xx or v1.y.xx	-
	Boot service 'Pro' version	V2.0.0 or 2.0.0	EE8D
	Scale server 'Pro' version	V2.y.xx or 2.y.xx	-
	Boot service 'Pro' WPF version	V3.0.xx or 3.0.xx	B827409295
	Scale server 'Pro' WPF version	3.y.xx	-



OIML Member State
The Netherlands

Number R76/2006-A-NL1-20.21 revision 1
Project number 2512549
Page 3 of 3

	ScaleLock	V1.1.xx	
	Scale module 'IDNet or Rainbow'	V1.1.xx	
	Scale module 'POWERCELL'	V1.xx.yyyy	

Remark: 1, The letters x, y and z in version number are not relevant for legal metrology and can be represented by numbers or letters.

Software:

- The identification number will be displayed after pressing the following button:
 - 'Classic' version: 
 - 'Pro' version and 'Pro' WPF version: 

Revision History

This revision replaces the previous version.

Revision	Date	Changes
Initial	29-06-2020	-
1	24-12-2020	Changed boot service ID