

This OIML Certificate is issued under scheme A.

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

+**OIML R 76** - Edition 2006 for accuracy class $^{(\mathrm{III})}$

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority



NMi Certin B.V. Thijsseweg 11 2629 JA Delft The Netherlands T +31 88 6362332 certin@nmi.nl www.nmi.nl

NMi Certin B.V., OIML Issuing Authority NL1 14 April 2022

Certification Board

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon on top of the electronic version of this certificate.







-

OIML Member State The Netherlands

OIML Certificate



Number R76/2006-A-NL1-22.11 revision 0 Project number 2822921 Page 2 of 2

The conformity was established by the results of tests and examinations provided in the associated OIML Type Evaluation Reports:

No. NMi-2822921-01 dated 14 April 2022 that includes 51 pages;

No. NMi-2822921-02 dated 14 April 2022 that includes 18 pages.

Characteristics of the non-automatic weighing instrument:

| Accuracy class | |
|---|---|
| Maximum capacity | 15 kg ≤ Max ≤ 30 kg |
| Verification scale interval | e ≥ 2 g |
| Weighing ranges | Single interval Multi-interval |
| Maximum number of scale intervals (multi-interval) | n ≤ 3000 divisions (per partial weighing range) |
| Maximum number of partial weighing ranges | 2 |
| Tare | $T \leq$ -50% for instruments with one weighing range $T \leq$ - Max_1 for multi-interval instruments |
| Temperature range | 0 °C / +40 °C |
| Power supply voltage | 100 – 230 V AC 50/60 Hz |
| Application | Intended to be used for direct sales to the public |
| Software Version number identification | 03.02.xx (xx is a number between 01 and 99) (03.02 represents the legally relevant software) |

Revision History

| Revision | Date | Change(s) | |
|----------|------------|-----------|--|
| Initial | 2022-04-14 | - | |