

OIML Member State
The Netherlands

Number R117/1995-NL1-09.03
Project number 812653
Page 1 of 1

Issuing authority	NMi Certin B.V. Person responsible: C. Oosterman
Applicant	Tokheim Route de Soliers, 14540 Gretheville BP 268, Caen Cedex 14013 France
Manufacturer	Tokheim Route de Soliers, 14540 Gretheville BP 268, Caen Cedex 14013 France
Identification of the certified type	A Fuel Dispenser for Motor Vehicles Type : Quantum XXXX
Characteristics	Q_{max} : 80 L/min

The detailed characteristics will be defined in the Annex

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Evaluation Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R117 - Edition 1995 for accuracy class 0,5
OIML R118 - Edition 1995

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Evaluation Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority **NMi Certin B.V., OIML Issuing Authority NL1**
30 November 2009


C. Oosterman
Head Certification Board

The conformity was established by the results of tests and examinations provided in the associated OIML Evaluation Report(s):

for the TQM meter:

- No. CPC-810762-01;
- No. CPC-702138.

for the TQP-RS gas elimination device:

- No. CPC-809675-01.

for the TMC v4 calculating / indicating device:

- No. CPC-608298.

Characteristics of fuel dispensers for Motor Vehicles, model "Quantium XXXX":

with one "EPZ" Gas Elimination Device or one "TQP-RS" Gas Elimination Device and one "TQM" Measurement Transducer and one "TMC" calculating/indicating device:

Maximum flowrate L/min	Minimum flowrate L/min	Accuracy class	Minimum measured quantity L	Liquid	Maximum volume indication L	Maximum unit price EURO/L	Maximum price to pay EURO/L
80	2,0	0,5	2	gasoline/ gasoil	9999,99	9,999	9999,99

Comprising of: one or more measuring systems in the same housing.

Each measuring system consists of:

- One Tokheim, "TQP-RS" (EPZ with a high cover) combined pump and gas elimination device, or;
- One Tokheim, "TQP-RS" (EPZ with a lower top cover) combined pump and gas elimination device;
- One Tokheim, "TQM" measurement transducer;
- One Tokheim, "TMC" v4 calculating/indicating device.

One Tokheim combined pump and gas eliminator can be connected with two measurement transducers, each measuring transducer is considered as a part of a measuring system.

When more than one measuring system in one housing the "TMC" calculating/indicating device may be a common part of the measuring systems.

A Q_{max} of 80 L/min can be reached by connecting two gas separators and two measurement transducers in parallel with delivery via one hose with nozzle.

For multi-product dispensers it is only possible to deliver one product at the same time on one side of the dispenser.