

**OIML Member State**  
The Netherlands

Number R117/2007-NL1-16.03 revision 1  
Project number 1900481  
Page 1 of 6

Issuing authority  
Person responsible: NMi Certin B.V.  
C. Oosterman

Applicant and  
Manufacturer Dresser Wayne Pignone  
DEG Italia SpA  
Via Roma 32  
IT 23018 Talamona (SO)  
Italy

Identification of the  
certified type **A fuel dispenser**  
Type: Global Vista

Characteristics See page 2 and further

This Certificate attests the conformity of the above identified type (represented by the sample(s) identified in the OIML Type Evaluation Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

**R 117-1 (2007)** "Dynamic measuring systems for liquids other than water"

Accuracy class 0,5

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation identified above. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Type Evaluation Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority **NMi Certin B.V., OIML Issuing Authority NL1**  
14 February 2017



C. Oosterman  
Head Certification Board

NMi Certin B.V.  
Hugo de Grootplein 1  
3314 EG Dordrecht  
the Netherlands  
T +31 78 6332332  
[certin@nmi.nl](mailto:certin@nmi.nl)  
[www.nmi.nl](http://www.nmi.nl)

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at [www.oiml.org](http://www.oiml.org)

Reproduction of the complete document only is permitted.



**OIML Member State**  
The Netherlands

Number R117/2007-NL1-16.03 revision 1  
Project number 1900481  
Page 2 of 6

The conformity was established by the results of tests and examinations provided in the associated report(s):

- No. NMI-16200580-02 dated 18 November 2016 that includes 28 pages.

### Characteristics of the measuring instrument

In Table 1 the general characteristics of the measuring instrument are presented.  
The construction of the measuring instrument is recorded in the Documentation folder no. T10117-1.

**Table 1 General characteristics**

Flow rate range	See table 2
Minimum measured quantity	2 L
Maximum pressure	3,0 bar
Environmental classes	M1 / E1
Ambient temperature range	-25 °C / +55 °C; condensing humidity
Product temperature range	-25 °C / +50 °C
Intended for the measurement of	gasoline/gasoil or blend
Power supply voltage	230 / 400 V AC; 50 Hz

Each measuring instrument consists at least of:

- One combined pump and gas eliminator device (gas separator);
- One measurement transducer (meter);
- One calculating/indicating device (calculator).

The characteristics of the mentioned parts of the fuel dispenser are presented at table 3 and higher.

The same housing of the dispenser can comprise of one or more measuring systems. When more than one measuring systems are in one housing, one calculating/indicating device may be a common part of the measuring systems.

For multi-product dispensers it is only possible to deliver one product at the same time on one side of the dispenser.

Table 2 gives an overview of flow characteristics of the configurations of the family of instruments.

**Table 2 Flow characteristics of the configurations**

Configuration	Flow rate range	Remarks
1 x gas separator 1 x meter	4 – 70 L/min	Intended for the measurement of gasoline/gasoil.
1 x gas separator 1 x meter	4 – 40 L/min	Intended for the measurement of blending product.
1 x gas separator 1 x meter	4 – 40 L/min	Intended for the measurement of gasoline/gasoil. The gas separator of this measuring system is suitable for use with two measurement transducers. Each measuring transducer is considered as a part of a measuring system.
1 x gas separator 2 x meter	4 – 90 L/min	Intended for the measurement of gasoil. A Qmax of 90 L/min can also be reached by connecting two gas separators and two measurement transducers in parallel with delivery via one hose with nozzle. This configuration allows a delivery from two nozzles simultaneously at 90 L/min.
2 x gas separator 2 x meter	13 – 130 L/min	Intended for the measurement of gasoil. A Qmax of 90 L/min can be reached by connecting two measurement transducers in parallel with delivery via one hose with nozzle. This configuration does not allow a delivery from two nozzles simultaneously at 130 L/min (except when the remote pump is used).
3 x gas separator 4 x meter	13 – 130 L/min	Intended for the measurement of gasoil. This configuration allows a delivery from two nozzles at 130 L/min simultaneously.

**Production location**

The fuel dispenser is produced at one of the following production locations:

- Wayne Fueling Systems Sweden AB  
Hanögatan 10  
SE-211 24 Malmö  
Sweden
- Wayne Indústria e Comércio  
Estrada do Timbó, 126 – Higienópolis  
21061-280 – Rio de Janeiro  
Brazil
- Dresser Wayne Fuel Equipment (Shanghai-Puxi Branch Office) Co., Ltd  
F1, Building 2, No.511, Shanlian Road,  
Baoshan Shanghai  
China

**OIML Member State**  
The Netherlands

Number R117/2007-NL1-16.03 revision 1  
Project number 1900481  
Page 4 of 6

## Parts of the fuel dispenser

The conformity of the following parts was established by the results of tests and examinations provided in the associated report(s):

Part: Measurement transducer  
 Producer: Wayne Fueling Systems Sweden AB  
 Type: iMeter  
 Documentation folder: TC7211-1 and TC7212-6 (Pulsers)  
 Reports: No. NMI-16200580-02 dated 18 November 2016 that includes 28 pages.

**Table 3 General characteristics of the measurement transducer type iMeter**

Flow rate range [L/min]	3 – 70 L/min
MMQ	2 L
Maximum pressure	3,0 bar
Environmental classes	M1 / E1
Ambient temperature range	-25 °C / +55 °C
Product temperature range	-25 °C / +50 °C
Intended for the measurement of	low-viscosity mineral oils with a viscosity of 0,4 mPa·s – 8,0 mPa·s
Impulse encoder or pulser	WIP (WM001682-0001) or WIP (WM031856-0001) or XWIP (WM011529-0001) or XWIP II (WM019142-0001)

**OIML Member State**  
The Netherlands

Number R117/2007-NL1-16.03 revision 1  
Project number 1900481  
Page 5 of 6

Part: Calculating/indicating device  
 Producer: Wayne Fueling Systems Sweden AB  
 Type: iGEM  
 Documentation folder: TC7212-6  
 Reports: No. NMI-16200580-02 dated 18 November 2016 that includes 28 pages.

**Table 4 General characteristics of the calculating/indicating device**

Maximum volume indication	6 digits
Maximum unit price	4 or 5 digits
Maximum price to pay	6 or 7 digits
Environmental classes	M1 / E1
Ambient temperature range	-40 °C / +55 °C
Software identification	Checksum: 0BE5 or 555F
Impulse encoder or pulser	WIP (WM001682-0001) or WIP (WM031856-0001) or XWIP (WM011529-0001) or XWIP II (WM019142-0001)

Part: Gas elimination device  
 Producer: Wayne Fueling Systems Sweden AB  
 Type: CPU  
 Documentation folder: TC7210-1  
 Reports: No. NMI-16200580-02 dated 18 November 2016 that includes 28 pages.

**Table 5 General characteristics of the gas elimination device**

Maximum flow rate	90 L/min
Minimum pressure	1,2 bar
Maximum pressure	3,0 bar
Environmental classes	M1
Ambient temperature range	-25 °C / +55 °C
Product temperature range	-25 °C / +50 °C
Intended for the measurement of	low-viscosity mineral oils with a viscosity of 0,4 mPa·s – 8,0 mPa·s



# OIML Certificate of Conformity

**OIML Member State**  
The Netherlands

Number R117/2007-NL1-16.03 revision 1  
Project number 1900481  
Page 6 of 6

**Certificate history:**

This revision replaces the previous version.

Revision	Date	Description of the modification
Initial	18 August 2016	
1	14 February 2017	New company address and upgrade to new MID 2014/32/EU