



Member State
Denmark

OIML Certificate N°
R134/2006-DK3-13.01

OIML CERTIFICATE OF CONFORMITY

Issuing authority

Name: DELTA
Address: Venlighedsvej 4
2970 Hørsholm
Denmark

Person responsible: J. Hovgaard Jensen

Applicant

Name: Tunaylar Baskül Sanayi ve Ticaret A.Ş.
Address: Akçaburgaz Mah. 88 Sok. No:7
Esenyurt - İstanbul
Turkey

Manufacturer

of the certified pattern: Tunaylar Baskül Sanayi ve Ticaret A.Ş.

Identification

of the certified pattern: **Automatic instrument for weighing road vehicles in motion**
Type: LL2/AW
Further characteristics are set out on page 2.

This certificate attests the conformity of the above mentioned pattern (represented by the samples identified in the associated test report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

R134 edition 2006,

This certificate relates only to the metrological and technical characteristics of the pattern of the instrument concerned, as covered by the relevant OIML International Recommendation.

This certificate does not bestow any form of legal international approval.

Page 1. This certificate includes 2 pages



OIML Certificate N° R134/2006-DK3-13.01

The conformity was established by tests described in the associated test reports from
DELTA, DK, no. DANAK-1913637, dated 03 December 2013, 52 pages.
DELTA, DK, no. DANAK-1910532, dated 27 May 2009, 66 pages.
DELTA, DK, no. DANAK-199782, dated 14 October 2005, 76 pages.

The issuing authority: **DELTA, OIML Issuing Authority DK3**
6 December 2013

J. Hovgaard Jensen
Certification Officer

Characteristics

Accuracy class, total weight		1	2
Accuracy class, single axle load		C or D	C or D or E
Accuracy class, axle-group load		B or C or D	C or D or E
Maximum capacity	Max	≤ 30 000 kg	
Minimum capacity	Min	≥ 50×d	≥ 10×d
Scale interval	d	≤ 20 kg	≤ 50 kg
Number of verification scale intervals	n	500 ≤ n ≤ 3000	50 ≤ n ≤ 1000
Maximum operation speed	v _{max}	9 km/h	
Minimum operation speed	v _{min}	1 km/h	
Maximum transit speed:		30 km/h	
Maximum number of axles:	a _{max}	15	
Direction of travel		dual	
Scale interval for stationary load	E	≥ 0.8 μV	
Power supply voltage:		12 V _{DC}	
Connected load cells		Shall comply with R60	
Temperature range for the indicator		-10 °C / +40 °C	
Software version for LL2/AW		1.93.xx	

Important note:

Apart from the mention of the certificate's reference number and the name of the OIML Member State in which the certificate was issued, partial quotation of the certificate or of the associated test report is not permitted, though they may be reproduced in full.