



Member State
Denmark

OIML Certificate N°
R134/2006-DK3-14.03

OIML CERTIFICATE OF CONFORMITY

Issuing authority

Name: **DELTA**
Address: Venlighedsvej 4
2970 Hørsholm
Denmark

Person responsible: J. Hovgaard Jensen

Applicant

Name: **Giropes SL.**
Address: Pol. Empordà Internacional
C/Molló 15-16
E-17469 Vilamalla (Girona)
SPAIN

Manufacturer

of the certified pattern: **Giropes SL.**

Identification

of the certified pattern: **Automatic instrument for weighing road vehicles in motion**
Type: GesDyn GI308 BPPEM
Further characteristics are set out on page 2.

This certificate attests the conformity of the above mentioned pattern (represented by the samples identified in the associated test report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

R134 edition 2006

This certificate relates only to the metrological and technical characteristics of the pattern of the instrument concerned, as covered by the relevant OIML International Recommendation.

This certificate does not bestow any form of legal international approval.


Page 1. This certificate includes 2 pages



OIML Certificate N° R134/2006-DK3-14.03

The conformity was established by tests described in the associated test reports from DELTA, DK, no. DANAK-1913959, that includes 42 pages

The issuing authority: **DELTA, OIML Issuing Authority DK3**
14 March 2014


J. Hovgaard Jensen
Certification Officer

Characteristics

| | | | |
|-------------------------------------|------------|---------------------------|-----------|
| Accuracy class for vehicle mass | | 5 | |
| Accuracy class for single axle load | | E | |
| Maximum capacity | Max | 15 000 kg | 30 000 kg |
| Minimum capacity | Min | $\geq 10 \times d$ | |
| Scale interval | d | 20 kg | 50 kg |
| Maximum operation speed | v_{\max} | 4 km/h | |
| Minimum operation speed | v_{\min} | 1 km/h | |
| Maximum transit speed: | | 15 km/h | |
| Maximum number of axles: | | ≤ 10 | |
| Direction of travel | | Dual | |
| Scale interval for stationary load | e | $\geq 0.5 \mu V$ | |
| Power supply voltage: | | 100 - 240 V _{DC} | |
| Connected load cells | | 4 GIP C3 20t | |
| Temperature range for the indicator | | -10 °C / +40 °C | |
| Software version | GI308 | 1.0.0.x | |
| | GesDyn | 1.0.y.z | |

Important note:

Apart from the mention of the certificate's reference number and the name of the OIML Member State in which the certificate was issued, partial quotation of the certificate or of the associated test report is not permitted, though they may be reproduced in full.