



OIML Member State

Czech Republic

OIML Certificate No. R137/2012-A-CZ1-24.04

OIML CERTIFICATE ISSUED UNDER SCHEME A

OIML Issuing Authority

Name: Czech Metrology Institute

Address: Okružní 31, 638 00 Brno

Czech Republic

Person responsible: Jan Kalandra

Applicant

Name: Hanwei Electronics Group Corporation

Address: No.169 Xuesong Road, National High-Tech Zone

450001 Zhengzhou

China

Manufacturer

Name: Hanwei Electronics Group Corporation

Address: No.169 Xuesong Road, National High-Tech Zone

450001 Zhengzhou

China

Identification of the certified type (the detailed characteristics will be defined in the additional pages)

diaphragm gas meter

type: ARJ1.6-SA, ARJ2.5-SA (G1.6., G2.5)

Designation of the module (if applicable)

This OIML Certificate attests the conformity of the above identified type (represented by the sample(s) identified in the OIML type evaluation report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R137 Edition (year): 2012, Including Amendment 2014

For accuracy class (if applicable): 1.5



This OIML Certificate relates only to metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML Recommendation identified above.

This OIML Certificate does not bestow any form of legal international approval.

The conformity was established by the results of tests and examinations provided in the associated OIML type evaluation report:

- No. 0511-ER- P104-24 dated 18.9.2024 that includes 18 pages.
- Test Report No. 5012-PT-A0006-23 dated 5.6.2023 that includes 20 pages.

The technical documentation relating to the identified type is contained in documentation file: 0511-UL- P104-24

OIML Certificate History

Revision No.	Date	Description of the modification
-	25 September 2024	Issuing Certificate

Identification, signature and stamp

The OIML Issuing Authority

RNDr. Pavel Klenovský Head of Certification Body

Date: 25 September 2024

Cesty

Teules

Important note:


Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate is issued, partial quotation of the Certificate and of the associated OIML type evaluation report(s) is not permitted, although either may be reproduced in full.

1 General information concerning the type


Information, indicated on the instrument				
Manufacturer's trade mark	HOWEST			
Type designation	ARJ1.6-SA, ARJ2.5-SA (G1.6., G2.5)			
Accuracy class	1.5			
Cyclic volume (if applicable)	0.9 dm3			
Minimum pressure pmin	0 bar(g)			
Maximum pressure pmax	0.5 bar(g)			
Ambient temperature range	(-25 +55) °C			
Gas temperature range	(-25 +55) °C			
Base pressure (if applicable)	Not applicable			
Base temperature (if applicable)	Not applicable			
tsp (if applicable)	Not applicable			
Electrical power	Not applicable			
Identification of software	Not applicable			

Example of the labels:

Black



Black



Red



Photos of the constructions:



2 Additional information concerning the type


Size G	Q _{max} (m ³ /h)	Q_t (m ³ /h)	$Q_{min} \ (ext{m}^3/ ext{h})$	Cyclic volume V (dm³)	Maximum permissible pressure loss ΔP in Q_{max} (Pa)	Pmax (kPa)
G2.5	4.0	0.4	0.025	0.9	200	50
G1.6	2.5	0.25	0.016	0.9	200	50

The gas meter can be produced with the distance between connections (male threads): 130 mm, 110 mm, 90 mm

The male threads used in gas meters ARJ1.6-SA, ARJ2.5-SA (G1.6., G2.5): M30x2, G7/8", G3/4"




Dimensions of diaphragm gas meters ARJ1.6-SA, ARJ2.5-SA (G1.6., G2.5) (part 1/2)





Dimensions of diaphragm gas meters ARJ1.6-SA, ARJ2.5-SA (G1.6., G2.5) (part 2/2)





Location of 8 seals on diaphragm gas meters ARJ1.6-SA, ARJ2.5-SA (G1.6., G2.5):

