

OIML Member State
The Netherlands

Number R137/2012-NL1-15.09 revision 3
Project number 16200582
Page 1 of 4

Issuing authority
Person responsible: NMI Certin B.V.
C. Oosterman

Applicant and
Manufacturer Emerson Automation Solutions
11100 Brittmoore Park Drive
77041 Houston, Texas
United States of America

Manufacturers
mark or name Daniel Measurement and Control, Inc.

Identification of the
certified type An **ultrasonic Gas Meter**
3414 / 3415 / 3416 / 3417 Senior Sonic

Characteristics See page 2 and further

This Certificate attests the conformity of the above identified type (represented by the sample(s) identified in the OIML Type Evaluation Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

R 137-1 (2012) "Gas meters"

Accuracy class 0,5

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation identified above. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Type Evaluation Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority **NMI Certin B.V., OIML Issuing Authority NL1**
21 June 2017



C. Oosterman
Head Certification Board



OIML Certificate of Conformity

OIML Member State
The Netherlands

Number R137/2012-NL1-15.09 revision 3
Project number 16200582
Page 2 of 4

The conformity was established by the results of tests and examinations provided in the associated report(s):

- No. NMI-15200787-01 dated 25 February 2016 that includes 50 pages;
- No. NMI-16200582-02 dated 3 November 2016 that includes 7 pages.

Characteristics of the measuring instrument

In Table 1 the general characteristics of the measuring instrument are presented.
Table 2 gives an overview of the general characteristics of the family of instruments.
The construction of the measuring instrument is recorded in the Documentation folder no. T10078-5.

Gas meter configuration

Model 3414

The model 3414 is equipped with 4 measuring paths in a horizontal configuration.

Model 3415

The model 3415 contains of a model 3414 path layout and electronics. The model 3415 is additionally equipped with one check path which is connected to a separate set of electronics.

Model 3416

The model 3416 contains of a model 3414 path layout and electronics. The model 3416 is additionally equipped with one check path and one diagnostic path which are connected to a separate set of electronics.

Model 3417

The model 3417 is composed of two model 3414 electronics and transducers built into a model 3417 spool piece. The meter can be used in the following configurations:

1. Two separate gas meters
2. Pay / check configuration

Table 1 General characteristics

Destined for the measurement of	Gas volume	
Environmental classes	M2 / E2	
Accuracy class	Class 0,5	
Maximum pressure	425 bar	
Ambient temperature range	Tranducer type	Temperature range
	T11 T12 T21 T22 T41	-10°C / +55°C -10°C / +55°C -10°C / +55°C -40°C / +55°C -40°C / +55°C



OIML Certificate of Conformity

OIML Member State
The Netherlands

Number R137/2012-NL1-15.09 revision 3
Project number 16200582
Page 3 of 4

Gas temperature range	Tranducer type	Temperature range
	T11	-20°C / +55°C
	T12	-20°C / +55°C
	T21	-20°C / +55°C
	T22	-40°C / +55°C
T41	-50°C / +100°C	
Designed for	Condensing humidity	
Orientation	All orientations	
Power supply voltage	10,4 – 36 V DC	
Software identification	Version number: 1.24 Checksum: 1869761847 Version number: 1.27 Checksum: 2717395331	

Table 2 General characteristics of the family of instruments

Diameter		V_{min} [m/s]	V_t [m/s]	V_{max} [m/s]
DN [mm]	Typical ranges [mm]			
100	80 ~ 108	0,5	$1/10 V_{max}$	28
150	124 ~ 161			
200	173 ~ 212			
250	216 ~ 265			
300	257 ~ 315			
350	284 ~ 343			30,5
400	325 ~ 394			
450	367 ~ 445			
500	408 ~ 495			
600	491 ~ 597			
750	730 ~ 749	26		
900	876 ~ 899	23		
1050	1029 ~ 1048	21		



OIML Certificate of Conformity

OIML Member State
The Netherlands

Number R137/2012-NL1-15.09 revision 3
Project number 16200582
Page 4 of 4

Installation conditions:

Inlet piping and flow straightener
The meter is used in the following configuration:

- 5D piping followed by a CPA 55E straightener followed by 10D piping at the inlet of the meter, see document 10078/0-10.

Certificate history:

This revision replaces the previous version.

Revision	Date	Description of the modification
Initial	6 November 2015	-
1	4 March 2016	Class 0,5 and Vmin lowered to 0,5m/s
2	3 November 2016	Additional electronic boards and Modules are added
3	21 June 2017	Correction installation conditions