



Number R21/2007-A-NL1-22.03 revision 0 Project number 2550883 Page 1 of 3

Issuing authority

NMi Certin B.V.

Person responsible: M.Ph.D. Schmidt

Applicant and Manufacturer

Interfacom S.A.U.

Torrent de l'Estadella 64 08030 Barcelona

Spain

Identification of the certified type

Taximeter

Type:

TX80

Characteristics

See following page(s)

This OIML Certificate is issued under scheme A.

This Certificate attests the conformity of the above identified type (represented by the sample(s) identified in the OIML Type Evaluation Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):



R 21 (2007) "Taximeters"

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation identified above. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Type Evaluation Report(s) is not permitted, although either may be reproduced in full.

NMi Certin B.V., OIML Issuing Authority NL1

27 December 2022

Certification Board

NMi Certin B.V. Thijsseweg 11 2629 JA Delft the Netherlands T +31 88 636 2332 certin@nmi.nl www.nmi.nl

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon at the top of the electronic version of this certificate.














OIML Certificate



The conformity was established by the results of tests and examinations provided in the associated reports:

- No. NMi-1900283-01 dated 29 January 2018 that includes 35 pages;
- No. NMi-2227413-01 dated 19 October 2018 that includes 9 pages;
- No. NMi-2385038-01 dated 4 March 2020 that includes 38 pages;
- No. NMi-2550827-01 dated 1 February 2021 that includes 25 pages;
- No. NMi-2385039-01 dated 9 March 2021 that includes 32 pages;
- No. NMi-2385039-02 dated 9 March 2021 that includes 36 pages;
- No. NMi-2385039-03 dated 9 March 2021 that includes 35 pages;
- No. NMi-2550883-01 dated 23 December 2022 that includes 35 pages.

Characteristics of the measuring instrument

Electromagnetic immunity class		E3		
Mechanical environment class		M3		
Climatic environment	temperature range	-25 °C / +70 °C		
	humidity	condensing		
	intended location	closed		
		Range	Resolution	
Distance signal generator constant k [km ⁻¹]		500 to 80000	1	
Time tariff [CU/h]		0,01 to 359964	0,01	
Distance tariff [CU/km]		0,01 to 99990	0,01	
CU = Currency Uni	t			
Time measuring signal frequency		10 Hz		
Power supply voltage		9 – 16 V DC		

Software identification	ı		
Part	Version	Checksum	Remark
TX 80	2.08 2.10 2.32 2.44 2.46	9E02 B894 EF73 8EA8 92E4	Unit that measures distance and time and does the fare calculation
Skyglass	2.01 2.02 2.04 2.05	E48D 4089 3D46 3153	User interface (display) also applicable for Pro variant
Urba / Urba One	2.02 2.03	4089 0F70	User interface (display)
Sherpan / Sherpan +	2.02	4089	User interface (display) also applicable for Pro variant

The construction of the measuring instrument is recorded in the Documentation folder no. T10881-7.









Number R21/2007-A-NL1-22.03 revision 0 Project number 2550883 Page 3 of 3

Revision History

+	Revision	Date	Change(s)
	0	27 December 2022	Initial issue.









