

OIML Member State
The Netherlands

Number R46/2012-A-NL1-22.01 revision 1
Project number 2557963
Page 1 of 3

Issuing authority NMI Certin B.V.
Person responsible: M.Ph.D. Schmidt

Manufacturer Globaltronics
Address Lot 120, CPC Industrial Park, Northen extension area
12573/48, 6 October City, Giza
Country Egypt

Identification of the certified type An **active electrical energy meter**
Type: GE300-SS

Characteristics See page 2 and further

This OIML Certificate is issued under scheme A

This Certificate attests the conformity of the above identified type (represented by the sample(s) identified in the OIML Type Evaluation Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

R 46-1/-2 (2012) "Active electrical energy meters"

Accuracy class B

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation identified above. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Type Evaluation Report is not permitted, although either may be reproduced in full.

Issuing Authority **NMI Certin B.V., OIML Issuing Authority NL1**
7 July 2023

Certification Board

The conformity was established by the results of tests and examinations provided in the associated report:

- No. NMI-2557963-01 dated 8 March 2022 that includes 56 pages.

Characteristics of the measuring instrument

In Table 1 the general characteristics of the measuring instrument are presented. The construction of the measuring instrument is recorded in the Documentation folder no. R46-2012-A-NL1-22.01-1.

Table 1 General characteristics

General characteristics	
Meter type	static
Connection mode (phase, wires, elements)	3p, 4w, 3e
Direction of energy flow / registers	One-register, bi-directional.
Terminal arrangement	DIN
Protective class	Category 2
Impulse voltage	8 kV
Environmental application	
Ambient temperature range	-40 °C to +70°C and 75 °C (3k7)
Humidity class	H3
IP Rating / environmental use	IP54 / outdoor
Meter quantities	
Nominal voltage (U_{nom})	3x230/400 V
Nominal frequency (f_{nom})	60 Hz
Maximum current (I_{max})	100 A
Transitional current (I_{tr})	1 A ($I_b = 10$ A)
Minimum current (I_{min})	0,25 A
Starting current (I_{st})	0,04 A
Meter constant	1.000 imp./kWh
Product version	
Hardware version	GE300-S_V1.0_03-2020
Software identification	Version number: KSA_GE300-SS_V1.0-03-20_V1.0.0_04-2021 Checksum: 70B48E8B



OIML Member State
The Netherlands

OIML Certificate

Number R46/2012-A-NL1-22.01 revision 1
Project number 2557963
Page 3 of 3

Certificate history:

This revision replaces the previous version.

Revision	Date	Description of the modification
Initial	2022-03-08	-
1	2023-07-07	Impulse voltage level included