





**OIML Member State** 

The Netherlands

Number R46/2012-A-NL1-23.04 revision 0 Project number 3630882 Page 1 of 4

Issuing authority NMi Certin B.V.

Person responsible: M.Ph.D. Schmidt

Applicant and Saudi Meters Company Itd. Manufacturer 2nd Industrial Area

4719 Riyadh 14331 -7141 Unit No. 14

Kingdom of Saudi Arabia

Identification of the A measuring instrument

certified type Type: MA309MT3LSA or MA309MT4LSA

Characteristics See page 2 and further.

This OIML Certificate is issued under scheme A.

This Certificate attests the conformity of the above identified type (represented by the sample(s) identified in the OIML Type Evaluation Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

R 46-1/-2 (2012) "Active electrical energy meters"

C for MA309MT4LSA Accuracy class

Accuracy class D for MA309MT3LSA

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation identified above. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Type Evaluation Report(s) is not permitted, although either may be reproduced in full.

NMi Certin B.V., OIML Issuing Authority NL1 **Issuing Authority** 

8 September 2023

Certification Board





NMi Certin B.V. Thijsseweg 11 2629 JA Delft The Netherlands T+31 88 636 2332 certin@nmi.nl www.nmi.nl

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon at the top of the electronic version of this certificate.











Number R46/2012-A-NL1-23.04 revision 0 Project number 3630882 Page 2 of 4



The conformity was established by the results of tests and examinations provided in the associated reports:

- No. NMi-3630882-03 dated 8 September 2023 that includes 60 pages;
- No. NMi-3630882-04 dated 8 September 2023 that includes 12 pages.

#### **Characteristics of the measuring instrument**

In Table 1 the general characteristics of the measuring instrument are presented.

#### **Table 1 General characteristics**

General characteristics MA309MT3LSA		
Meter type	Static	
Connection mode (phase, wires, elements)	3p, 3w, 2e (CT/VT connected)	
Direction of energy flow / registers	Two-registers, bi-directional	
Terminal arrangement	DIN 43857	
Protective class	Category 2	
Environmental application		
Ambient temperature range	-25 °C to +70 °C	
Humidity class	H2	
IP Rating / environmental use	IP54 (indoor)	
Meter quantities		
Nominal voltage (U <sub>nom</sub> )	3x110V	
Nominal frequency (f <sub>nom</sub> )	60 Hz	
Maximum current (I <sub>max</sub> )	6 A	
Basic current (I <sub>n</sub> )	1 A or 1.5 A	
Transitional current (I <sub>tr</sub> )	0.1 A	
Minimum current (I <sub>min</sub> )	0.01 A or 0.015 A	
Starting current (I <sub>st</sub> )	0.001 A or 0.0015 A	
Meter constant	10.000 imp./kWh	
Product version		
Hardware version	KF13A430 Main V1.1	
Power supply board (PS)	KF13A430 PS V1.1	
Module version	CL101KG: KF01L064 V3.4	







**OIML Member State** The Netherlands

Number R46/2012-A-NL1-23.04 revision 0 Project number 3630882 Page 3 of 4



Software identification	LR: 4303 Checksum: 7741D0E8

General characteristics MA309MT4LSA		
Meter type	Static	
Connection mode (phase, wires, elements)	3p, 4w, 3e (CT connected)	
Direction of energy flow / registers	Two-registers, bi-directional	
Terminal arrangement	DIN 43857	
Protective class	Category 2	
Environmental application		
Ambient temperature range	-25 °C to +70 °C	
Humidity class	H2	
IP Rating / environmental use	IP54 (indoor)	
Meter quantities	,	
Nominal voltage ( $U_{\text{nom}}$ )	3x133/230V3x230/400V	
Nominal frequency (f <sub>nom</sub> )	60 Hz	
Maximum current (I <sub>max</sub> )	6 A	
Basic current (In)	1.5 A	
Transitional current (/tr)	0.1 A	
Minimum current (/ <sub>min</sub> )	0.015 A	
Starting current (I <sub>st</sub> )	0.0015 A	
Meter constant	10.000 imp./kWh	
Product version		
Hardware version	KF13A427 Main V1.1	
Power supply board (PS)	KF13A427 PS V1.1	
Module version	CL101KG: KF01L064 V3.4	
Software identification	LR: 4202 Checksum: E893748D	









**OIML Member State** The Netherlands

Number R46/2012-A-NL1-23.04 revision 0 Project number 3630882 Page 4 of 4



### **Certificate history:**



Revision	Date	Description of the modification
0	8 September 2023	Initial issue









