



OIML Certificate

OIML Member StateThe Netherlands



Number R60/2017-A-NL1-23.14 revision 0 Project number 3622963 Page 1 of 3

Issuing authority NMi Certin B.V.

Person responsible: M.Ph.D. Schmidt

Applicant and Xiamen Loadcell Technology Co., Ltd. (LCT)
Manufacturer 5FL, No. 20, Huli Park

Tongan Industry Central Zone

361100 Xiamen

China

Identification of the

certified type

A **single point load cell**, with strain gauges, equipped with electronics.

Registered trade name : LCT

Type : LAD series

Characteristics See next page

This OIML Certificate is issued under scheme A.

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 60-1:2017 for accuracy class C

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.



Issuing Authority

NMi Certin B.V., OIML Issuing Authority NL1 2 May 2023



This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon on top of the electronic version of this certificate.







Thijsseweg 11 2629 JA Delft The Netherlands T +31 88 6362332 certin@nmi.nl







OIML Certificate

OIML Member StateThe Netherlands



Number R60/2017-A-NL1-23.14 revision 0 Project number 3622963 Page 2 of 3

The conformity was established by the results of tests and examinations provided in the associated reports:

- No. NMi-3622963-01 dated 28 April 2023 that includes 51 pages;
- No. NMi-3622963-02 dated 28 April 2023 that includes 46 pages.

Characteristics of the load cell:

Characterization of load cell capabilities	Analog-passive load cell		
Maximum capacity (E _{max})	60 kg up to and including 1500 kg		
Minimum dead load	0 kg		
Accuracy Class	С		
Rated Output	2,0 mV/V ±10%		
Maximum number of load cell intervals (n) (1)	6000		
Ratio of minimum LC Verification interval $^{(1)}$ Y = E_{max} / v_{min}	15000		
Ratio of minimum dead load output return $^{(1)}$ Z = E_{max} / (2 * DR)	10000		
Input impedance	405 Ω ± 10 Ω		
Temperature range	-10 °C / + 40 °C		
Fraction p _{LC}	0,7		
Humidity Class	СН		
Safe overload	150 % of E _{max}		
Output impedance	350 Ω ± 5 Ω		
Recommended excitation	5-12 V AC / DC		
Excitation maximum	18 V AC / DC		
Transducer material	Aluminium		
Atmospheric protection	Silicon rubber		

Remarks:

1. The characteristics for n_{max} , Y and Z can be reduced separately.

Each load cell produced is provided with an accompanying document with information about its characteristics.

The above identified Type (represented by the sample(s) identified in the OIML Test Report) have been found to comply with the additional national requirements established by the United States of America (NIST Handbook 44 and NCWM Publication 14), included in the Utilizer Declaration:

- R 60 OIML-CS rev.2 Additional requirements from the United States Accuracy class III L;
- R 60 OIML-CS rev.2 Additional requirements from the United States Marking requirements.







OIML Member State The Netherlands



Number R60/2017-A-NL1-23.14 revision 0 Project number 3622963 Page 3 of 3

Revision History



Ī	Revision	Date	Change(s)
	0	2023-05-02	Initial issue.









