



OIML Certificate





Number R60/2021-A-NL1-24.30 revision 0 Project number 3819083 Page 1 of 3

Issuing authority NMi Certin B.V.

Person responsible: M.Ph.D. Schmidt

Applicant and Società Cooperativa Bilanciai Campogalliano Manufacturer Via S.Ferrari n.16

41011 Campogalliano (MO)

Italy

Identification of the

certified type

A **compression load cell**, with strain gauges, equipped with electronics.

Registered trade name Società Cooperativa Bilanciai

Campogalliano

Type CPD-TD

Characteristics See next page

This OIML Certificate is issued under scheme A.

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 60-1:2021 for accuracy class C

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority

NMi Certin B.V., OIML Issuing Authority NL1 25 November 2024



This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon on top of the electronic version of this certificate.







NMi Certin B.V. Thiissewea 11 2629 JA Delft The Netherlands T +31 88 6362332 certin@nmi.nl www.nmi.nl







OIML Certificate

OIML Member State The Netherlands



Number R60/2021-A-NL1-24.30 revision 0 Project number 3819083 Page 2 of 3

The conformity was established by the results of tests and examinations provided in the associated report(s):

No. NMi-3819083-01 dated 25 November 2024 that includes 94 pages.

Characteristics of the load cell:

Characterization of	load cell capabilities	Digital load cell			
Maximum capacity (E _{max})		20 t up to and including 100 t			
Minimum dead loa	d	0 kg			
Accuracy Class		С			
Maximum number of load cell intervals (n) (1)		6000			
Ratio of minimum LC Verification interval $^{(1)}$ Y = E_{max} / v_{min}		18000			
Ratio of minimum dead load output return (1) $Z = E_{max} / (2 * DR)$		6000			
Temperature range		-10 °C / +40 °C			
Fraction p_{LC}		0,8			
Humidity Class		СН			
Safe overload		150 % of E _{max}			
Recommended excitation		10 - 18 V DC			
Excitation maximum		18 V DC			
Transducer material		Stainless steel			
Atmospheric protection		Hermetically welded			
Electromagnetic environment class		E2			
Number of counts for E _{max}		200000 ≥ Y * 5 / p _{LC}			
	Software id	491411			
Software identification	Version number	1.01			
	Checksum	0x327FC9AB			
-					

Remark:

1. The characteristics for n_{max} , Y and Z can be reduced separately.

its

Each load cell produced is provided with an accompanying document with information about its characteristics.





OIML Certificate

OIML Member StateThe Netherlands



Number R60/2021-A-NL1-24.30 revision 0 Project number 3819083 Page 3 of 3

The above identified Type (represented by the sample(s) identified in the OIML Test Report) have been found to comply with the additional national requirements established by the United States of America (NIST Handbook 44 and NCWM Publication 14), included in the Utilizer Declaration:

- R 60 OIML-CS rev.2 Additional requirements from the United States Accuracy class III L;
- R 60 OIML-CS rev.2 Additional requirements from the United States Marking requirements.

Revision History

Revision	Date	Change(s)		
0	2024-11-25	Initial issue.		







