



OIML Certificate

OIML Member State The Netherlands



Number R60/2021-A-NL1-24.34 revision 1 Project number 3817525 Page 1 of 3

Issuing authority NMi Certin B.V.

Person responsible: M.Ph.D. Schmidt

Applicant and Zhonghang Electronic Measuring Instruments (Xi'an) Co., Ltd. Manufacturer Xinyuan Road, north part of EDZ Hanzhong

723000, Hanzhong, Shaanxi

China

Identification of the

certified type

A **compression load cell**, with strain gauges, equipped with electronics.

Registered trade name : ZEMIC

DHM14Hx Type

Characteristics See next page

This OIML Certificate is issued under scheme A.


This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 60-1:2021 for accuracy class C

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority





Certification Board

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon on top of the electronic version of this certificate.







NMi Certin B.V. Thiissewea 11 2629 JA Delft The Netherlands T +31 88 6362332 certin@nmi.nl www.nmi.nl







OIML Certificate

OIML Member StateThe Netherlands



Number R60/2021-A-NL1-24.34 revision 1 Project number 3817525 Page 2 of 3

The conformity was established by the results of tests and examinations provided in the associated report:

- No. NMi-3817525-01 revision 1 dated 20 January 2025 that includes 95 pages.

Characteristics of the load cell:

characteristics of the load cen.			
Characterization of load cell capabilities	Digital load cell		
Maximum capacity (E _{max})	10 t up to and including 50 t		
Minimum dead load	0 kg		
Accuracy Class	С		
Maximum number of load cell intervals (n) (1)	4000		
Ratio of minimum LC Verification interval $^{(1)}$ Y = E_{max} / v_{min}	20000		
Ratio of minimum dead load output return (1) $Z = E_{max} / (2 * DR)$	4000		
Temperature range	-10 °C / + 40 °C		
Fraction p _{LC}	0,7		
Humidity Class	СН		
Safe overload	150 % of E _{max}		
Recommended excitation	12 V DC		
Excitation maximum	15 V DC		
Transducer material	Alloy steel		
Atmospheric protection	Hermetically welded		
Electromagnetic environment class	E2		
Number of counts for E _{max}	300000 ≥ Y * 5 / p _{LC}		
Software identification	Version number: 6.0 Checksum: 8FBF		

Remark:

1. The characteristics for n_{max} , Y and Z can be reduced separately.

Each load cell produced is provided with an accompanying document with information about its characteristics.

The above identified Type (represented by the sample(s) identified in the OIML Test Report) have been found to comply with the additional national requirements established by the United States of America (NIST Handbook 44 and NCWM Publication 14), included in the Utilizer Declaration:

- R 60 OIML-CS rev.2 Additional requirements from the United States Accuracy class III L;
- R 60 OIML-CS rev.2 Additional requirements from the United States Marking requirements.





OIML Member State The Netherlands



Number R60/2021-A-NL1-24.34 revision 1 Project number 3817525 Page 3 of 3

Revision History



Revision	Date	Change(s)
0	2024-12-30	Initial issue.
1	2025-01-21	Editorial change in the applicant's name









