



#### **OIML Member State**

Japan

OIML Certificate No. R76/2006-A-JP1-22.01 Revision 1

# OIML CERTIFICATE ISSUED UNDER SCHEME A

**OIML** Issuing Authority

National Metrology Institute of Japan /National Institute of Name:

Advanced Industrial Science and Technology (NMIJ/AIST)

AIST Tsukuba Central 3, 1-1-1 Umezono Tsukuba Ibaraki Address:

305-8563, Japan

Person responsible: ISHIMURA Kazuhiko, President of AIST

**Applicant** 

A&D Company, Limited Name:

3-23-14 Higashi-ikebukuro, Toshima-ku, Tokyo 170-0013 JAPAN Address:

Manufacturer

A&D Manufacturing Company, Limited Name:

Hidaka Factory

Address: 7-5, Harajyuku, Hidaka-shi, Saitama-ken 350-1205, JAPAN

A&D SCALES CO., LTD. Name:

191, Inseok-ro, Deoksan-myeon, Jincheon-gun, Address:

Chungcheongbuk-do, 27856, KOREA

Identification of the certified type (the detailed characteristics will be defined in the additional pages)

Models:

FG-CWP series, FG-ACWP series

**Designation of the module** (if applicable)

Non-automatic weighing instruments

This OIML Certificate attests the conformity of the above identified type (represented by the sample(s) identified in the OIML type evaluation report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

**OIML R 76-1, Edition: 2006** 

For accuracy class: (III)

This OIML Certificate relates only to metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML Recommendation identified above.

This OIML Certificate does not bestow any form of legal international approval.

The conformity was established by the results of tests and examinations provided in the associated OIML type evaluation reports:

No. 2024-001, dated 19 Aug 2024, that includes 8 pages

The technical documentation relating to the identified type is contained in documentation files:

· No. 2024-001-D, dated 19 Aug 2024

# **OIML Certificate History**

Revision No.	Date	Description of the modification	
Revision 0	31 October 2022	OIML Certificate first issued	
Revision 1	21 August 2024	Added model FG-ACWP series	
=	/-	-	

This revision replaces previous versions of the certificate.

Identification, signature and stamp

The Issuing Authority
NMIJ/AIST

The CIML Member



ISHIMURA Kazuhiko President of AIST

21 August 2024



**OTA Akihiro** 

21 August 2024

#### The accreditation body:

NMIJ/AIST has achieved accreditation under the ASNITE-Product (OIML) scheme of IAJapan, which applies ISO/IEC 17065:2012 and regulations relevant to OIML-CS as the accreditation criteria. The accreditation identification for this accreditation is ASNITE 0001 Product and the details of the accreditation information could be referred from the IAJapan website (https://www.nite.go.jp/en/iajapan/asnite/lab/index.html).

#### Important note:

Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate is issued, partial quotation of the Certificate and of the associated OIML type evaluation report(s) is not permitted, although either may be reproduced in full.

#### **DESCRIPTIVE ANNEX**

## Characteristics of the instrument:

The FG-CWP series and FG-ACWP series are class III, self-indicating, non-automatic weighing instrument. The instruments are not designed for direct sales to the public.

## Technical data:

Туре	FG-30KCMWP	FG-60KCLWP	FG-150KCLWP
	FG-30KACMWP	FG-60KACLWP	FG-150KACLWP
Class			
Max	30 kg	60 kg	150 kg
е	0.01 kg	0.02 kg	0.05 kg
Min	0.2 kg	0.4 kg	1 kg
Temperature range	-10 to 40 ℃		

## Device:

- Initial zero-setting device (≤ 20 % of Max)
- Semi-automatic zero-setting device (≤ 4 % of Max)
- Zero-tracking (≤ 4 % of Max)
- Semi-automatic subtractive tare weighing (T = Max)
- Zero indicator
- · Indication of stable equilibrium device

## Interface:

Bluetooth communication interface (to connect Personal computer)

## Software:

The legally relevant software is designated version P-1.xx, with x reflecting non-legally relevant changes.

#### Sealing:

Access to the calibration switch is prevented by a tamper-evident lead and wire type seal.